CERTEX | Lifting Solutions Group
Axel Johnson International

# Dynamometer 05T with remote control

**Product information**



REMA®

### Mechanical properties

- Aluminum housing.
- Alloy steel pulling unit.
- Test load 2 x WLL (without losing accuracy).
- Safety factor 5 x WLL.
- International Protection Rating / Ingress Protection: IP65 (EN60529).

### Electrical specifications

- Alkaline battery (3 x AA type).
- Battery operating time about 180 hours.

### Electronic specifications

- Operating temperature range between -5 ° C to + 55 ° C.
- Accuracy up to approx. 0.1% of the reading value.
- Battery indicator.

### Standard delivery

- Bow shackles (3,2T and 6,3T).
- Remote control to tare.

### Option

- Bow shackle from 10T.

... *Read more*

**Marking:** According to standard, CE-mark
**Standard:** EN 12100, EN 13155, EN 13889
**Note:** Includes plastic case, manual and calibration report.


**Safety factor:** 5

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

# Dynamometer 05T with remote control

## Blueprint



## Technical data

| Part code | GTIN No. | WLL ton | Model | Shackle size | Resolution kg | A mm | B mm | C mm | D mm | E mm | F mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 60971514005 | 8717365110986 | 3.2 | DSD05T-3.2T | 3.25t in. | 1 | 199 | 69 | 130 | 25 | 269 | 20 | 4.7 |
| 60971514007 | 8717365110993 | 6.3 | DSD05T-6.3T | 6.5t in. | 2 | 213 | 69 | 144 | 35 | 348 | 26 | 7 |
| 60971514009 | 8717365112003 | 10 | DSD05T-10.0T | 12t ex. | 5 | 265 | 100 | 181 | 50 | 455 | 36 | 9.6 |

© November 2026 - All Rights Reserved