



1 leg REMA-10- RML-RCX-RCH

Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

1 leg REMA-10 | masterlink RML | connecting link RCX | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality.

Marking: According to standard, CE-marked

Standard: EN 1677-1, DIN 17115, DIN 5692, EN 818-7

Safety factor: 4

Grade: 10

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	Model	Weight kg	Delivery time
R2691106-1	8717365150722	6	1.4	1	1400KG-6MM-RML-RCH-1M	1.7	3
R2691106-1.5	8717365150739	6	1.4	1.5	1400KG-6MM-RML-RCH-1,5M	2.1	3
R2691106-2	8717365150746	6	1.4	2	1400KG-6MM-RML-RCH-2M	2.5	3
R2691106-2.5	8717365150753	6	1.4	2.5	1400KG-6MM-RML-RCH-2,5M	2.9	3

R2691106-3	8717365150760	6	1.4	3	1400KG-6MM-RML-RCH-3M	3.3	3
R2691106-3.5	8717365150777	6	1.4	3.5	1400KG-6MM-RML-RCH-3,5M	3.7	3
R2691106-4	8717365150784	6	1.4	4	1400KG-6MM-RML-RCH-4M	4.1	3
R2691108-1	8717365150791	8	2.5	1	2500KG-8MM-RML-RCH-1M	2.9	3
R2691108-1.5	8717365150807	8	2.5	1.5	2500KG-8MM-RML-RCH-1,5M	3.65	3
R2691108-2	8717365150814	8	2.5	2	2500KG-8MM-RML-RCH-2M	4.4	3
R2691108-2.5	8717365150821	8	2.5	2.5	2500KG-8MM-RML-RCH-2,5M	5.15	3
R2691108-3	8717365150838	8	2.5	3	2500KG-8MM-RML-RCH-3M	5.9	3
R2691108-3.5	8717365150845	8	2.5	3.5	2500KG-8MM-RML-RCH-3,5M	6.65	3
R2691108-4	8717365150852	8	2.5	4	2500KG-8MM-RML-RCH-4M	7.4	3
R2691110-1	8717365150869	10	4	1	4000KG-10MM-RML-RCH-1M	4.6	3
R2691110-1.5	8717365150876	10	4	1.5	4000KG-10MM-RML-RCH-1,5M	5.75	3
R2691110-2	8717365150883	10	4	2	4000KG-10MM-RML-RCH-2M	6.9	3
R2691110-2.5	8717365150890	10	4	2.5	4000KG-10MM-RML-RCH-2,5M	8.05	3
R2691110-3	8717365150906	10	4	3	4000KG-10MM-RML-RCH-3M	9.2	3
R2691110-3.5	8717365150913	10	4	3.5	4000KG-10MM-RML-RCH-3,5M	10.35	3
R2691110-4	8717365150920	10	4	4	4000KG-10MM-RML-RCH-4M	11.5	3
R2691113-1	8717365150937	13	6.7	1	6700KG-13MM-RML-RCH-1M	8.6	3
R2691113-1.5	8717365150944	13	6.7	1.5	6700KG-13MM-RML-RCH-1,5M	10.6	3
R2691113-2	8717365150951	13	6.7	2	6700KG-13MM-RML-RCH-2M	12.6	3
R2691113-2.5	8717365150968	13	6.7	2.5	6700KG-13MM-RML-RCH-2,5M	14.6	3
R2691113-3	8717365150975	13	6.7	3	6700KG-13MM-RML-RCH-3M	16.6	3
R2691113-3.5	8717365150982	13	6.7	3.5	6700KG-13MM-RML-RCH-3,5M	18.6	3

R2691113-4	8717365150999	13	6.7	4	6700KG-13MM-RML-RCH-4M	20.6	3
R2691116-1	8717365151002	16	10	1	10T-16MM-RML-RCH-1M	13.8	3
R2691116-1.5	8717365151019	16	10	1.5	10T-16MM-RML-RCH-1,5M	16.8	3
R2691116-2	8717365151026	16	10	2	10T-16MM-RML-RCH-2M	19.8	3
R2691116-2.5	8717365151033	16	10	2.5	10T-16MM-RML-RCH-2,5M	22.8	3
R2691116-3	8717365151040	16	10	3	10T-16MM-RML-RCH-3M	25.8	3
R2691116-3.5	8717365151057	16	10	3.5	10T-16MM-RML-RCH-3,5M	28.8	3
R2691116-4	8717365151064	16	10	4	10T-16MM-RML-RCH-4M	31.8	3