



1 leg REMA-10-RML-RDG-RCS

Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

1 leg REMA-10 | masterlink RML | clevis shortening hook RDG | self locking clevis hook RCS



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality.

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 5692, DIN 17115

Safety factor: 4

Grade: 10

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	Model	Weight kg	Delivery time
R2691406-1	8717365151774	6	1.4	1	1400KG-6MM-RDG-RCS-1M	2.2	3
R2691406-1.5	8717365151781	6	1.4	1.5	1400KG-6MM-RDG-RCS-1,5M	2.6	3
R2691406-2	8717365151798	6	1.4	2	1400KG-6MM-RDG-RCS-2M	3	3
R2691406-2.5	8717365151804	6	1.4	2.5	1400KG-6MM-RDG-RCS-2,5M	3.4	3

R2691406-3	8717365151811	6	1.4	3	1400KG-6MM-RDG-RCS-3M	3.8	3
R2691406-3.5	8717365151828	6	1.4	3.5	1400KG-6MM-RDG-RCS-3,5M	4.2	3
R2691406-4	8717365151835	6	1.4	4	1400KG-6MM-RDG-RCS-4M	4.6	3
R2691408-1	8717365151842	8	2.5	1	2500KG-8MM-RDG-RCS-1M	3.6	3
R2691408-1.5	8717365151859	8	2.5	1.5	2500KG-8MM-RDG-RCS-1,5M	4.35	3
R2691408-2	8717365151866	8	2.5	2	2500KG-8MM-RDG-RCS-2M	5.1	3
R2691408-2.5	8717365151873	8	2.5	2.5	2500KG-8MM-RDG-RCS-2,5M	5.85	3
R2691408-3	8717365151880	8	2.5	3	2500KG-8MM-RDG-RCS-3M	6.6	3
R2691408-3.5	8717365151897	8	2.5	3.5	2500KG-8MM-RDG-RCS-3,5M	7.35	3
R2691408-4	8717365151903	8	2.5	4	2500KG-8MM-RDG-RCS-4M	8.1	3
R2691410-1	8717365151910	10	4	1	4000KG-10MM-RDG-RCS-1M	6.1	3
R2691410-1.5	8717365151927	10	4	1.5	4000KG-10MM-RDG-RCS-1,5M	7.25	3
R2691410-2	8717365151934	10	4	2	4000KG-10MM-RDG-RCS-2M	8.4	3
R2691410-2.5	8717365151941	10	4	2.5	4000KG-10MM-RDG-RCS-2,5M	9.55	3
R2691410-3	8717365151958	10	4	3	4000KG-10MM-RDG-RCS-3M	10.7	3
R2691410-3.5	8717365151965	10	4	3.5	4000KG-10MM-RDG-RCS-3,5M	11.85	3
R2691410-4	8717365151972	10	4	4	4000KG-10MM-RDG-RCS-4M	13	3
R2691413-1	8717365151989	13	6.7	1	6700KG-13MM-RDG-RCS-1M	11.6	3
R2691413-1.5	8717365151996	13	6.7	1.5	6700KG-13MM-RDG-RCS-1,5M	13.6	3
R2691413-2	8717365152009	13	6.7	2	6700KG-13MM-RDG-RCS-2M	15.6	3
R2691413-2.5	8717365152016	13	6.7	2.5	6700KG-13MM-RDG-RCS-2,5M	17.6	3
R2691413-3	8717365152023	13	6.7	3	6700KG-13MM-RDG-RCS-3M	19.6	3
R2691413-3.5	8717365152030	13	6.7	3.5	6700KG-13MM-RDG-RCS-3,5M	21.6	3

R2691413-4	8717365152047	13	6.7	4	6700KG-13MM-RDG-RCS-4M	23.6	3
R2691416-1	8717365152054	16	10	1	10T-16MM-RDG-RCS-1M	19.6	3
R2691416-1.5	8717365152061	16	10	1.5	10T-16MM-RDG-RCS-1,5M	22.6	3
R2691416-2	8717365152078	16	10	2	10T-16MM-RDG-RCS-2M	25.6	3
R2691416-2.5	8717365152085	16	10	2.5	10T-16MM-RDG-RCS-2,5M	28.6	3
R2691416-3	8717365152092	16	10	3	10T-16MM-RDG-RCS-3M	31.6	3
R2691416-3.5	8717365152108	16	10	3.5	10T-16MM-RDG-RCS-3,5M	34.6	3
R2691416-4	8717365152115	16	10	4	10T-16MM-RDG-RCS-4M	37.6	3