

Chain sling assemblies 2-leg REMA-10-RML-RCX-RCS

Product information



REMA[®]

The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

2 leg REMA-10 chain | masterlink RML | connecting link RCX | self locking clevis hook RCS



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: DIN 17115, DIN 5692, EN 1677-1, EN 818-7

Safety factor: 4

Grade: 10

Chain sling assemblies 2-leg REMA-10-RML-RCX-RCS

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
R2692206-1	8717365152474	6	1.96	1	1.96	1,4	1960KG-6MM-RML-RCS-1M	3.3
R2692206-1.5	8717365152481	6	1.96	1.5	1.96	1,4	1960KG-6MM-RML-RCS-1,5M	4.1
R2692206-2	8717365152498	6	1.96	2	1.96	1,4	1960KG-6MM-RML-RCS-2M	4.9
R2692206-2.5	8717365152504	6	1.96	2.5	1.96	1,4	1960KG-6MM-RML-RCS-2,5M	5.7
R2692206-3	8717365152511	6	1.96	3	1.96	1,4	1960KG-6MM-RML-RCS-3M	6.5
R2692206-3.5	8717365152528	6	1.96	3.5	1.96	1,4	1960KG-6MM-RML-RCS-3,5M	7.3
R2692206-4	8717365152535	6	1.96	4	1.96	1,4	1960KG-6MM-RML-RCS-4M	8.1
R2692208-1	8717365152542	8	3.5	1	3.5	2,5	3500KG-8MM-RML-RCS-1M	5.8
R2692208-1.5	8717365152559	8	3.5	1.5	3.5	2,5	3500KG-8MM-RML-RCS-1,5M	7.3
R2692208-2	8717365152566	8	3.5	2	3.5	2,5	3500KG-8MM-RML-RCS-2M	8.8
R2692208-2.5	8717365152573	8	3.5	2.5	3.5	2,5	3500KG-8MM-RML-RCS-2,5M	10.3
R2692208-3	8717365152580	8	3.5	3	3.5	2,5	3500KG-8MM-RML-RCS-3M	11.8
R2692208-3.5	8717365152597	8	3.5	3.5	3.5	2,5	3500KG-8MM-RML-RCS-3,5M	13.3
R2692208-4	8717365152603	8	3.5	4	3.5	2,5	3500KG-8MM-RML-RCS-4M	14.8
R2692210-1	8717365152610	10	5.6	1	5.6	4	5600KG-10MM-RML-RCS-1M	9.6
R2692210-1.5	8717365152627	10	5.6	1.5	5.6	4	5600KG-10MM-RML-RCS-1,5M	11.9
R2692210-2	8717365152634	10	5.6	2	5.6	4	5600KG-10MM-RML-RCS-2M	14.2
R2692210-2.5	8717365152641	10	5.6	2.5	5.6	4	5600KG-10MM-RML-RCS-2,5M	16.5
R2692210-3	8717365152658	10	5.6	3	5.6	4	5600KG-10MM-RML-RCS-3M	18.8
R2692210-3.5	8717365152665	10	5.6	3.5	5.6	4	5600KG-10MM-RML-RCS-3,5M	21.1
R2692210-4	8717365152672	10	5.6	4	5.6	4	5600KG-10MM-RML-RCS-4M	23.4
R2692213-1	8717365152689	13	9.38	1	9.38	6,7	9380KG-13MM-RML-RCS-1M	17.8
R2692213-1.5	8717365152696	13	9.38	1.5	9.38	6,7	9380KG-13MM-RML-RCS-1,5M	21.8
R2692213-2	8717365152702	13	9.38	2	9.38	6,7	9380KG-13MM-RML-RCS-2M	25.8
R2692213-2.5	8717365152719	13	9.38	2.5	9.38	6,7	9380KG-13MM-RML-RCS-2,5M	29.8
R2692213-3	8717365152726	13	9.38	3	9.38	6,7	9380KG-13MM-RML-RCS-3M	33.8
R2692213-3.5	8717365152733	13	9.38	3.5	9.38	6,7	9380KG-13MM-RML-RCS-3,5M	37.8
R2692213-4	8717365152740	13	9.38	4	9.38	6,7	9380KG-13MM-RML-RCS-4M	41.8
R2692216-1	8717365152757	16	14	1	14	10	14T-16MM-RML-RCS-1M	31.4
R2692216-1.5	8717365152764	16	14	1.5	14	10	14T-16MM-RML-RCS-1,5M	37.4
R2692216-2	8717365152771	16	14	2	14	10	14T-16MM-RML-RCS-2M	43.4

Chain sling assemblies 2-leg REMA-10-RML-RCX-RCS

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
R2692216-2.5	8717365152788	16	14	2.5	14	10	14T-16MM-RML-RCS-2,5M	49.4
R2692216-3	8717365152795	16	14	3	14	10	14T-16MM-RML-RCS-3M	55.4
R2692216-3.5	8717365152801	16	14	3.5	14	10	14T-16MM-RML-RCS-3,5M	61.4
R2692216-4	8717365152818	16	14	4	14	10	14T-16MM-RML-RCS-4M	67.4