



Chain sling assy 2-leg REMA-10-RML-RDG-RCH

Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

2-leg REMA-10 chain | masterlink RML | clevis shortening hook RDG | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality.

Marking: According to standard, CE-marked

Standard: DIN 17115, DIN 5692, EN 1677-1, EN 818-7

Safety factor: 4

Grade: 10

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg	Delivery time
R2692306-1	8717365152825	6	1.96	1	1.96	1,4	1960KG-6MM-RDG-RCH-1M	3.5	3
R2692306-1.5	8717365152832	6	1.96	1.5	1.96	1,4	1960KG-6MM-RDG-RCH-1,5M	4.3	3
R2692306-2	8717365152849	6	1.96	2	1.96	1,4	1960KG-6MM-RDG-RCH-2M	5.1	3
R2692306-2.5	8717365152856	6	1.96	2.5	1.96	1,4	1960KG-6MM-RDG-RCH-2,5M	5.9	3

R2692306-3	8717365152863	6	1.96	3	1.96	1,4	1960KG-6MM-RDG-RCH-3M	6.7	3
R2692306-3.5	8717365152870	6	1.96	3.5	1.96	1,4	1960KG-6MM-RDG-RCH-3,5M	7.5	3
R2692306-4	8717365152887	6	1.96	4	1.96	1,4	1960KG-6MM-RDG-RCH-4M	8.3	3
R2692308-1	8717365152894	8	3.5	1	3.5	2,5	3500KG-8MM-RDG-RCH-1M	6.8	3
R2692308-1.5	8717365152900	8	3.5	1.5	3.5	2,5	3500KG-8MM-RDG-RCH-1,5M	8.3	3
R2692308-2	8717365152917	8	3.5	2	3.5	2,5	3500KG-8MM-RDG-RCH-2M	9.8	3
R2692308-2.5	8717365152924	8	3.5	2.5	3.5	2,5	3500KG-8MM-RDG-RCH-2,5M	11.3	3
R2692308-3	8717365152931	8	3.5	3	3.5	2,5	3500KG-8MM-RDG-RCH-3M	12.8	3
R2692308-3.5	8717365152948	8	3.5	3.5	3.5	2,5	3500KG-8MM-RDG-RCH-3,5M	14.3	3
R2692308-4	8717365152955	8	3.5	4	3.5	2,5	3500KG-8MM-RDG-RCH-4M	15.8	3
R2692310-1	8717365152962	10	5.6	1	5.6	4	5600KG-10MM-RDG-RCH-1M	11.8	3
R2692310-1.5	8717365152979	10	5.6	1.5	5.6	4	5600KG-10MM-RDG-RCH-1,5M	14.1	3
R2692310-2	8717365152986	10	5.6	2	5.6	4	5600KG-10MM-RDG-RCH-2M	16.4	3
R2692310-2.5	8717365152993	10	5.6	2.5	5.6	4	5600KG-10MM-RDG-RCH-2,5M	18.7	3
R2692310-3	8717365153006	10	5.6	3	5.6	4	5600KG-10MM-RDG-RCH-3M	21	3
R2692310-3.5	8717365153013	10	5.6	3.5	5.6	4	5600KG-10MM-RDG-RCH-3,5M	23.3	3
R2692310-4	8717365153020	10	5.6	4	5.6	4	5600KG-10MM-RDG-RCH-4M	25.6	3
R2692313-1	8717365153037	13	9.38	1	9.38	6,7	9380KG-13MM-RDG-RCH-1M	21	3
R2692313-1.5	8717365153044	13	9.38	1.5	9.38	6,7	9380KG-13MM-RDG-RCH-1,5M	25	3
R2692313-2	8717365153051	13	9.38	2	9.38	6,7	9380KG-13MM-RDG-RCH-2M	29	3
R2692313-2.5	8717365153068	13	9.38	2.5	9.38	6,7	9380KG-13MM-RDG-RCH-2,5M	33	3
R2692313-3	8717365153075	13	9.38	3	9.38	6,7	9380KG-13MM-RDG-RCH-3M	37	3
R2692313-3.5	8717365153082	13	9.38	3.5	9.38	6,7	9380KG-13MM-RDG-RCH-3,5M	41	3

R2692313-4	8717365153099	13	9.38	4	9.38	6,7	9380KG-13MM-RDG-RCH-4M	45	3
R2692316-1	8717365153105	16	14	1	14	10	14T-16MM-RDG-RCH-1M	36.2	3
R2692316-1.5	8717365153112	16	14	1.5	14	10	14T-16MM-RDG-RCH-1,5M	42.2	3
R2692316-2	8717365153129	16	14	2	14	10	14T-16MM-RDG-RCH-2M	48.2	3
R2692316-2.5	8717365153136	16	14	2.5	14	10	14T-16MM-RDG-RCH-2,5M	54.2	3
R2692316-3	8717365153143	16	14	3	14	10	14T-16MM-RDG-RCH-3M	60.2	3
R2692316-3.5	8717365153150	16	14	3.5	14	10	14T-16MM-RDG-RCH-3,5M	66.2	3
R2692316-4	8717365153167	16	14	4	14	10	14T-16MM-RDG-RCH-4M	72.2	3