



## Chain sling assy 2-leg REMA-10-RML-RDG-RCS

### Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

2 leg REMA-10 chain | masterlink RML | clevis shortening hook RDG | self locking clevis hook RCS



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality.

**Marking:** According to standard, CE-marked

**Standard:** DIN 17115, DIN 5692, EN 1677-1, EN 818-7

**Safety factor:** 4

**Grade:** 10

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg	Delivery time
R2692406-1	8717365153174	6	1.96	1	1.96	1,4	1960KG-6MM-RDG-RCS-1M	3.9	3
R2692406-1.5	8717365153181	6	1.96	1.5	1.96	1,4	1960KG-6MM-RDG-RCS-1,5M	4.7	3
R2692406-2	8717365153198	6	1.96	2	1.96	1,4	1960KG-6MM-RDG-RCS-2M	5.5	3
R2692406-2.5	8717365153204	6	1.96	2.5	1.96	1,4	1960KG-6MM-RDG-RCS-2,5M	6.3	3
R2692406-3	8717365153211	6	1.96	3	1.96	1,4	1960KG-6MM-RDG-RCS-3M	7.1	3
R2692406-3.5	8717365153228	6	1.96	3.5	1.96	1,4	1960KG-6MM-RDG-RCS-3,5M	7.9	3

R2692406-4	8717365153235	6	1.96	4	1.96	1,4	1960KG-6MM-RDG-RCS-4M	8.7	3
R2692408-1	8717365153242	8	3.5	1	3.5	2,5	3500KG-8MM-RDG-RCS-1M	7	3
R2692408-1.5	8717365153259	8	3.5	1.5	3.5	2,5	3500KG-8MM-RDG-RCS-1,5M	8.5	3
R2692408-2	8717365153266	8	3.5	2	3.5	2,5	3500KG-8MM-RDG-RCS-2M	10	3
R2692408-2.5	8717365153273	8	3.5	2.5	3.5	2,5	3500KG-8MM-RDG-RCS-2,5M	11.5	3
R2692408-3	8717365153280	8	3.5	3	3.5	2,5	3500KG-8MM-RDG-RCS-3M	13	3
R2692408-3.5	8717365153297	8	3.5	3.5	3.5	2,5	3500KG-8MM-RDG-RCS-3,5M	14.5	3
R2692408-4	8717365153303	8	3.5	4	3.5	2,5	3500KG-8MM-RDG-RCS-4M	16	3
R2692410-1	8717365153310	10	5.6	1	5.6	4	5600KG-10MM-RDG-RCS-1M	12.2	3
R2692410-1.5	8717365153327	10	5.6	1.5	5.6	4	5600KG-10MM-RDG-RCS-1,5M	14.5	3
R2692410-2	8717365153334	10	5.6	2	5.6	4	5600KG-10MM-RDG-RCS-2M	16.8	3
R2692410-2.5	8717365153341	10	5.6	2.5	5.6	4	5600KG-10MM-RDG-RCS-2,5M	19.1	3
R2692410-3	8717365153358	10	5.6	3	5.6	4	5600KG-10MM-RDG-RCS-3M	21.4	3
R2692410-3.5	8717365153365	10	5.6	3.5	5.6	4	5600KG-10MM-RDG-RCS-3,5M	23.7	3
R2692410-4	8717365153372	10	5.6	4	5.6	4	5600KG-10MM-RDG-RCS-4M	26	3
R2692413-1	8717365153389	13	9.38	1	9.38	6,7	9380KG-13MM-RDG-RCS-1M	22.4	3
R2692413-1.5	8717365153396	13	9.38	1.5	9.38	6,7	9380KG-13MM-RDG-RCS-1,5M	26.4	3
R2692413-2	8717365153402	13	9.38	2	9.38	6,7	9380KG-13MM-RDG-RCS-2M	30.4	3
R2692413-2.5	8717365153419	13	9.38	2.5	9.38	6,7	9380KG-13MM-RDG-RCS-2,5M	34.4	3
R2692413-3	8717365153426	13	9.38	3	9.38	6,7	9380KG-13MM-RDG-RCS-3M	38.4	3
R2692413-3.5	8717365153433	13	9.38	3.5	9.38	6,7	9380KG-13MM-RDG-RCS-3,5M	42.4	3
R2692413-4	8717365153440	13	9.38	4	9.38	6,7	9380KG-13MM-RDG-RCS-4M	46.4	3
R2692416-1	8717365153457	16	14	1	14	10	14T-16MM-RDG-RCS-1M	39.6	3
R2692416-1.5	8717365153464	16	14	1.5	14	10	14T-16MM-RDG-RCS-1,5M	45.6	3
R2692416-2	8717365153471	16	14	2	14	10	14T-16MM-RDG-RCS-2M	51.6	3
R2692416-2.5	8717365153488	16	14	2.5	14	10	14T-16MM-RDG-RCS-2,5M	57.6	3

R2692416-3	8717365153495	16	14	3	14	10	14T-16MM-RDG-RCS-3M	63.6	3
R2692416-3.5	8717365153501	16	14	3.5	14	10	14T-16MM-RDG-RCS-3,5M	69.6	3
R2692416-4	8717365153518	16	14	4	14	10	14T-16MM-RDG-RCS-4M	75.6	3