



## Chain sling assy 3-leg REMA-10-RMA-RCX-RCH

### Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

3 leg REMA-10 | masterlink RMA | connecting link RCX | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGV](#), ensuring a testament to its exceptional quality.

**Marking:** According to standard, CE-marked

**Standard:** EN 818-7, EN 1677-1, DIN 17115, DIN 5692

**Safety factor:** 4

**Grade:** 10

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg	Delivery time
R2693106-1	8717365153525	6	2.94	1	2.94	2,1	2940KG-6MM-RMA-RCH-1M	5	3
R2693106-1.5	8717365153532	6	2.94	1.5	2.94	2,1	2940KG-6MM-RMA-RCH-1,5M	6.2	3
R2693106-2	8717365153549	6	2.94	2	2.94	2,1	2940KG-6MM-RMA-RCH-2M	7.4	3
R2693106-2.5	8717365153556	6	2.94	2.5	2.94	2,1	2940KG-6MM-RMA-RCH-2,5M	8.6	3

R2693106-3	8717365153563	6	2.94	3	2.94	2,1	2940KG-6MM-RMA-RCH-3M	9.8	3
R2693106-3.5	8717365153570	6	2.94	3.5	2.94	2,1	2940KG-6MM-RMA-RCH-3,5M	11	3
R2693106-4	8717365153587	6	2.94	4	2.94	2,1	2940KG-6MM-RMA-RCH-4M	12.2	3
R2693108-1	8717365153594	8	5.25	1	5.25	3,75	5250KG-8MM-RMA-RCH-1M	9.6	3
R2693108-1.5	8717365153600	8	5.25	1.5	5.25	3,75	5250KG-8MM-RMA-RCH-1,5M	11.85	3
R2693108-2	8717365153617	8	5.25	2	5.25	3,75	5250KG-8MM-RMA-RCH-2M	14.1	3
R2693108-2.5	8717365153624	8	5.25	2.5	5.25	3,75	5250KG-8MM-RMA-RCH-2,5M	16.35	3
R2693108-3	8717365153631	8	5.25	3	5.25	3,75	5250KG-8MM-RMA-RCH-3M	18.6	3
R2693108-3.5	8717365153648	8	5.25	3.5	5.25	3,75	5250KG-8MM-RMA-RCH-3,5M	20.85	3
R2693108-4	8717365153655	8	5.25	4	5.25	3,75	5250KG-8MM-RMA-RCH-4M	23.1	3
R2693110-1	8717365153662	10	8.4	1	8.4	6	8400KG-10MM-RMA-RCH-1M	15	3
R2693110-1.5	8717365153679	10	8.4	1.5	8.4	6	8400KG-10MM-RMA-RCH-1,5M	18.45	3
R2693110-2	8717365153686	10	8.4	2	8.4	6	8400KG-10MM-RMA-RCH-2M	21.9	3
R2693110-2.5	8717365153693	10	8.4	2.5	8.4	6	8400KG-10MM-RMA-RCH-2,5M	25.35	3
R2693110-3	8717365153709	10	8.4	3	8.4	6	8400KG-10MM-RMA-RCH-3M	28.8	3
R2693110-3.5	8717365153716	10	8.4	3.5	8.4	6	8400KG-10MM-RMA-RCH-3,5M	32.25	3
R2693110-4	8717365153723	10	8.4	4	8.4	6	8400KG-10MM-RMA-RCH-4M	35.7	3
R2693113-1	8717365153730	13	14	1	14	10,05	14T-13MM-RMA-RCH-1M	27.2	3
R2693113-1.5	8717365153747	13	14	1.5	14	10,05	14T-13MM-RMA-RCH-1,5M	33.2	3
R2693113-2	8717365153754	13	14	2	14	10,05	14T-13MM-RMA-RCH-2M	39.2	3
R2693113-2.5	8717365153761	13	14	2.5	14	10,05	14T-13MM-RMA-RCH-2,5M	45.2	3
R2693113-3	8717365153778	13	14	3	14	10,05	14T-13MM-RMA-RCH-3M	51.2	3
R2693113-3.5	8717365153785	13	14	3.5	14	10,05	14T-13MM-RMA-RCH-3,5M	57.2	3

R2693113-4	8717365153792	13	14	4	14	10,05	14T-13MM-RMA-RCH-4M	63.2	3
R2693116-1	8717365153808	16	21	1	21	15	21T-16MM-RMA-RCH-1M	45.1	3
R2693116-1.5	8717365153815	16	21	1.5	21	15	21T-16MM-RMA-RCH-1,5M	54.1	3
R2693116-2	8717365153822	16	21	2	21	15	21T-16MM-RMA-RCH-2M	63.1	3
R2693116-2.5	8717365153839	16	21	2.5	21	15	21T-16MM-RMA-RCH-2,5M	72.1	3
R2693116-3	8717365153846	16	21	3	21	15	21T-16MM-RMA-RCH-3M	81.1	3
R2693116-3.5	8717365153853	16	21	3.5	21	15	21T-16MM-RMA-RCH-3,5M	90.1	3
R2693116-4	8717365153860	16	21	4	21	15	21T-16MM-RMA-RCH-4M	99.1	3