

Chain sling assy 3-leg REMA-10-RMA-RCX-RCH

Product information



REMA[®]

The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

3 leg REMA-10 | masterlink RMA | connecting link RCX | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 17115, DIN 5692

Safety factor: 4

Grade: 10

Chain sling assy 3-leg REMA-10-RMA-RCX-RCH

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
241126931061	8717365153525	6	2.94	1	2.94	2,1	2940KG-6MM-RMA-RCH-1M	5
2411269310615	8717365153532	6	2.94	1.5	2.94	2,1	2940KG-6MM-RMA-RCH-1,5M	6.2
241126931062	8717365153549	6	2.94	2	2.94	2,1	2940KG-6MM-RMA-RCH-2M	7.4
2411269310625	8717365153556	6	2.94	2.5	2.94	2,1	2940KG-6MM-RMA-RCH-2,5M	8.6
241126931063	8717365153563	6	2.94	3	2.94	2,1	2940KG-6MM-RMA-RCH-3M	9.8
2411269310635	8717365153570	6	2.94	3.5	2.94	2,1	2940KG-6MM-RMA-RCH-3,5M	11
241126931064	8717365153587	6	2.94	4	2.94	2,1	2940KG-6MM-RMA-RCH-4M	12.2
241126931081	8717365153594	8	5.25	1	5.25	3,75	5250KG-8MM-RMA-RCH-1M	9.6
2411269310815	8717365153600	8	5.25	1.5	5.25	3,75	5250KG-8MM-RMA-RCH-1,5M	11.85
241126931082	8717365153617	8	5.25	2	5.25	3,75	5250KG-8MM-RMA-RCH-2M	14.1
2411269310825	8717365153624	8	5.25	2.5	5.25	3,75	5250KG-8MM-RMA-RCH-2,5M	16.35
241126931083	8717365153631	8	5.25	3	5.25	3,75	5250KG-8MM-RMA-RCH-3M	18.6
2411269310835	8717365153648	8	5.25	3.5	5.25	3,75	5250KG-8MM-RMA-RCH-3,5M	20.85
241126931084	8717365153655	8	5.25	4	5.25	3,75	5250KG-8MM-RMA-RCH-4M	23.1
241126931101	8717365153662	10	8.4	1	8.4	6	8400KG-10MM-RMA-RCH-1M	15
2411269311015	8717365153679	10	8.4	1.5	8.4	6	8400KG-10MM-RMA-RCH-1,5M	18.45
241126931102	8717365153686	10	8.4	2	8.4	6	8400KG-10MM-RMA-RCH-2M	21.9
2411269311025	8717365153693	10	8.4	2.5	8.4	6	8400KG-10MM-RMA-RCH-2,5M	25.35
241126931103	8717365153709	10	8.4	3	8.4	6	8400KG-10MM-RMA-RCH-3M	28.8
2411269311035	8717365153716	10	8.4	3.5	8.4	6	8400KG-10MM-RMA-RCH-3,5M	32.25
241126931104	8717365153723	10	8.4	4	8.4	6	8400KG-10MM-RMA-RCH-4M	35.7
241126931131	8717365153730	13	14	1	14	10,05	14T-13MM-RMA-RCH-1M	27.2
2411269311315	8717365153747	13	14	1.5	14	10,05	14T-13MM-RMA-RCH-1,5M	33.2
241126931132	8717365153754	13	14	2	14	10,05	14T-13MM-RMA-RCH-2M	39.2
2411269311325	8717365153761	13	14	2.5	14	10,05	14T-13MM-RMA-RCH-2,5M	45.2
241126931133	8717365153778	13	14	3	14	10,05	14T-13MM-RMA-RCH-3M	51.2
2411269311335	8717365153785	13	14	3.5	14	10,05	14T-13MM-RMA-RCH-3,5M	57.2
241126931134	8717365153792	13	14	4	14	10,05	14T-13MM-RMA-RCH-4M	63.2
241126931161	8717365153808	16	21	1	21	15	21T-16MM-RMA-RCH-1M	45.1
2411269311615	8717365153815	16	21	1.5	21	15	21T-16MM-RMA-RCH-1,5M	54.1
241126931162	8717365153822	16	21	2	21	15	21T-16MM-RMA-RCH-2M	63.1

Chain sling assy 3-leg REMA-10-RMA-RCX-RCH

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
2411269311625	8717365153839	16	21	2.5	21	15	21T-16MM-RMA-RCH-2,5M	72.1
241126931163	8717365153846	16	21	3	21	15	21T-16MM-RMA-RCH-3M	81.1
2411269311635	8717365153853	16	21	3.5	21	15	21T-16MM-RMA-RCH-3,5M	90.1
241126931164	8717365153860	16	21	4	21	15	21T-16MM-RMA-RCH-4M	99.1