

## 3 leg REMA-10-RMA-RCX-RCS

### Product information



# REMA<sup>®</sup>

The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

3 leg REMA-10 chain | masterlink RMA | connecting link RCX | self locking clevis hook RCS



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

**Marking:** According to standard, CE-marked

**Standard:** EN 818-7, EN 1677-1, DIN 17115, DIN 5692

**Safety factor:** 4

**Grade:** 10

## 3 leg REMA-10-RMA-RCX-RCS

### Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
R2693206-1	8717365153877	6	2.94	1	2.94	2,1	2940KG-6MM-RMA-RCS-1M	5.6
R2693206-1.5	8717365153884	6	2.94	1.5	2.94	2,1	2940KG-6MM-RMA-RCS-1,5M	6.8
R2693206-2	8717365153891	6	2.94	2	2.94	2,1	2940KG-6MM-RMA-RCS-2M	8
R2693206-2.5	8717365153907	6	2.94	2.5	2.94	2,1	2940KG-6MM-RMA-RCS-2,5M	9.2
R2693206-3	8717365153914	6	2.94	3	2.94	2,1	2940KG-6MM-RMA-RCS-3M	10.4
R2693206-3.5	8717365153921	6	2.94	3.5	2.94	2,1	2940KG-6MM-RMA-RCS-3,5M	11.6
R2693206-4	8717365153938	6	2.94	4	2.94	2,1	2940KG-6MM-RMA-RCS-4M	12.8
R2693208-1	8717365153945	8	5.25	1	5.25	3,75	5250KG-8MM-RMA-RCS-1M	9.9
R2693208-1.5	8717365153952	8	5.25	1.5	5.25	3,75	5250KG-8MM-RMA-RCS-1,5M	12.15
R2693208-2	8717365153969	8	5.25	2	5.25	3,75	5250KG-8MM-RMA-RCS-2M	14.4
R2693208-2.5	8717365153976	8	5.25	2.5	5.25	3,75	5250KG-8MM-RMA-RCS-2,5M	16.65
R2693208-3	8717365153983	8	5.25	3	5.25	3,75	5250KG-8MM-RMA-RCS-3M	18.9
R2693208-3.5	8717365153990	8	5.25	3.5	5.25	3,75	5250KG-8MM-RMA-RCS-3,5M	21.15
R2693208-4	8717365154003	8	5.25	4	5.25	3,75	5250KG-8MM-RMA-RCS-4M	23.4
R2693210-1	8717365154010	10	8.4	1	8.4	6	8400KG-10MM-RMA-RCS-1M	15.6
R2693210-1.5	8717365154027	10	8.4	1.5	8.4	6	8400KG-10MM-RMA-RCS-1,5M	19.05
R2693210-2	8717365154034	10	8.4	2	8.4	6	8400KG-10MM-RMA-RCS-2M	22.5
R2693210-2.5	8717365154041	10	8.4	2.5	8.4	6	8400KG-10MM-RMA-RCS-2,5M	25.95
R2693210-3	8717365154058	10	8.4	3	8.4	6	8400KG-10MM-RMA-RCS-3M	29.4
R2693210-3.5	8717365154065	10	8.4	3.5	8.4	6	8400KG-10MM-RMA-RCS-3,5M	32.85
R2693210-4	8717365154072	10	8.4	4	8.4	6	8400KG-10MM-RMA-RCS-4M	36.3
R2693213-1	8717365154089	13	14	1	14	10,05	14T-13MM-RMA-RCS-1M	29.3
R2693213-1.5	8717365154096	13	14	1.5	14	10,05	14T-13MM-RMA-RCS-1,5M	35.3
R2693213-2	8717365154102	13	14	2	14	10,05	14T-13MM-RMA-RCS-2M	41.3
R2693213-2.5	8717365154119	13	14	2.5	14	10,05	14T-13MM-RMA-RCS-2,5M	47.3
R2693213-3	8717365154126	13	14	3	14	10,05	14T-13MM-RMA-RCS-3M	53.3
R2693213-3.5	8717365154133	13	14	3.5	14	10,05	14T-13MM-RMA-RCS-3,5M	59.3
R2693213-4	8717365154140	13	14	4	14	10,05	14T-13MM-RMA-RCS-4M	65.3
R2693216-1	8717365154157	16	21	1	21	15	21T-16MM-RMA-RCS-1M	50.2
R2693216-1.5	8717365154164	16	21	1.5	21	15	21T-16MM-RMA-RCS-1,5M	59.2
R2693216-2	8717365154171	16	21	2	21	15	21T-16MM-RMA-RCS-2M	68.2

## 3 leg REMA-10-RMA-RCX-RCS

### Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
R2693216-2.5	8717365154188	16	21	2.5	21	15	21T-16MM-RMA-RCS-2,5M	77.2
R2693216-3	8717365154195	16	21	3	21	15	21T-16MM-RMA-RCS-3M	86.2
R2693216-3.5	8717365154201	16	21	3.5	21	15	21T-16MM-RMA-RCS-3,5M	95.2
R2693216-4	8717365154218	16	21	4	21	15	21T-16MM-RMA-RCS-4M	104.2