



Chain sling assy 4-leg REMA-10-RMA-RCX-RCH

Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

4 leg REMA-10 | masterlink RMA | connecting link RCX | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality.

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 17115, DIN 5692

Safety factor: 4

Grade: 10

Part code	GTIN No.	Diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg	Delivery time
R2694106-1	8717365154928	6	2.94	1	2.94	2,1	2940KG-6MM-RMA-RCH-1M	6.2	3
R2694106-1.5	8717365154935	6	2.94	1.5	2.94	2,1	2940KG-6MM-RMA-RCH-1,5M	7.8	3
R2694106-2	8717365154942	6	2.94	2	2.94	2,1	2940KG-6MM-RMA-RCH-2M	9.4	3
R2694106-2.5	8717365154959	6	2.94	2.5	2.94	2,1	2940KG-6MM-RMA-RCH-2,5M	11	3

R2694106-3	8717365154966	6	2.94	3	2.94	2,1	2940KG-6MM-RMA-RCH-3M	12.6	3
R2694106-3.5	8717365154973	6	2.94	3.5	2.94	2,1	2940KG-6MM-RMA-RCH-3,5M	14.2	3
R2694106-4	8717365154980	6	2.94	4	2.94	2,1	2940KG-6MM-RMA-RCH-4M	15.8	3
R2694108-1	8717365154997	8	5.25	1	5.25	3,75	5250KG-8MM-RMA-RCH-1M	12	3
R2694108-1.5	8717365155000	8	5.25	1.5	5.25	3,75	5250KG-8MM-RMA-RCH-1,5M	15	3
R2694108-2	8717365155017	8	5.25	2	5.25	3,75	5250KG-8MM-RMA-RCH-2M	18	3
R2694108-2.5	8717365155024	8	5.25	2.5	5.25	3,75	5250KG-8MM-RMA-RCH-2,5M	21	3
R2694108-3	8717365155031	8	5.25	3	5.25	3,75	5250KG-8MM-RMA-RCH-3M	24	3
R2694108-3.5	8717365155048	8	5.25	3.5	5.25	3,75	5250KG-8MM-RMA-RCH-3,5M	27	3
R2694108-4	8717365155055	8	5.25	4	5.25	3,75	5250KG-8MM-RMA-RCH-4M	30	3
R2694110-1	8717365155062	10	8.4	1	8.4	6	8400KG-10MM-RMA-RCH-1M	18.8	3
R2694110-1.5	8717365155079	10	8.4	1.5	8.4	6	8400KG-10MM-RMA-RCH-1,5M	23.4	3
R2694110-2	8717365155086	10	8.4	2	8.4	6	8400KG-10MM-RMA-RCH-2M	28	3
R2694110-2.5	8717365155093	10	8.4	2.5	8.4	6	8400KG-10MM-RMA-RCH-2,5M	32.6	3
R2694110-3	8717365155109	10	8.4	3	8.4	6	8400KG-10MM-RMA-RCH-3M	37.2	3
R2694110-3.5	8717365155116	10	8.4	3.5	8.4	6	8400KG-10MM-RMA-RCH-3,5M	41.8	3
R2694110-4	8717365155123	10	8.4	4	8.4	6	8400KG-10MM-RMA-RCH-4M	46.4	3
R2694113-1	8717365155130	13	14	1	14	10,05	14T-13MM-RMA-RCH-1M	30.2	3
R2694113-1.5	8717365155147	13	14	1.5	14	10,05	14T-13MM-RMA-RCH-1,5M	38.2	3
R2694113-2	8717365155154	13	14	2	14	10,05	14T-13MM-RMA-RCH-2M	46.2	3
R2694113-2.5	8717365155161	13	14	2.5	14	10,05	14T-13MM-RMA-RCH-2,5M	54.2	3
R2694113-3	8717365155178	13	14	3	14	10,05	14T-13MM-RMA-RCH-3M	62.2	3
R2694113-3.5	8717365155185	13	14	3.5	14	10,05	14T-13MM-RMA-RCH-3,5M	70.2	3

R2694113-4	8717365155192	13	14	4	14	10,05	14T-13MM-RMA-RCH-4M	78.2	3
R2694116-1	8717365155208	16	21	1	21	15	21T-16MM-RMA-RCH-1M	56.5	3
R2694116-1.5	8717365155215	16	21	1.5	21	15	21T-16MM-RMA-RCH-1,5M	68.5	3
R2694116-2	8717365155222	16	21	2	21	15	21T-16MM-RMA-RCH-2M	80.5	3
R2694116-2.5	8717365155239	16	21	2.5	21	15	21T-16MM-RMA-RCH-2,5M	92.5	3
R2694116-3	8717365155246	16	21	3	21	15	21T-16MM-RMA-RCH-3M	104.5	3
R2694116-3.5	8717365155253	16	21	3.5	21	15	21T-16MM-RMA-RCH-3,5M	116.5	3
R2694116-4	8717365155260	16	21	4	21	15	21T-16MM-RMA-RCH-4M	128.5	3