

Chain sling assy 4-leg REMA-10-RMA-RCX-RCH

Product information



REMA[®]

The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

4 leg REMA-10 | masterlink RMA | connecting link RCX | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 17115, DIN 5692

Safety factor: 4

Grade: 10

Chain sling assy 4-leg REMA-10-RMA-RCX-RCH

Technical data

Part code	GTIN No.	Diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
241326941061	8717365154928	6	2.94	1	2.94	2,1	2940KG-6MM-RMA-RCH-1M	6.2
2413269410615	8717365154935	6	2.94	1.5	2.94	2,1	2940KG-6MM-RMA-RCH-1,5M	7.8
241326941062	8717365154942	6	2.94	2	2.94	2,1	2940KG-6MM-RMA-RCH-2M	9.4
2413269410625	8717365154959	6	2.94	2.5	2.94	2,1	2940KG-6MM-RMA-RCH-2,5M	11
241326941063	8717365154966	6	2.94	3	2.94	2,1	2940KG-6MM-RMA-RCH-3M	12.6
2413269410635	8717365154973	6	2.94	3.5	2.94	2,1	2940KG-6MM-RMA-RCH-3,5M	14.2
241326941064	8717365154980	6	2.94	4	2.94	2,1	2940KG-6MM-RMA-RCH-4M	15.8
241326941081	8717365154997	8	5.25	1	5.25	3,75	5250KG-8MM-RMA-RCH-1M	12
2413269410815	8717365155000	8	5.25	1.5	5.25	3,75	5250KG-8MM-RMA-RCH-1,5M	15
241326941082	8717365155017	8	5.25	2	5.25	3,75	5250KG-8MM-RMA-RCH-2M	18
2413269410825	8717365155024	8	5.25	2.5	5.25	3,75	5250KG-8MM-RMA-RCH-2,5M	21
241326941083	8717365155031	8	5.25	3	5.25	3,75	5250KG-8MM-RMA-RCH-3M	24
2413269410835	8717365155048	8	5.25	3.5	5.25	3,75	5250KG-8MM-RMA-RCH-3,5M	27
241326941084	8717365155055	8	5.25	4	5.25	3,75	5250KG-8MM-RMA-RCH-4M	30
241326941101	8717365155062	10	8.4	1	8.4	6	8400KG-10MM-RMA-RCH-1M	18.8
2413269411015	8717365155079	10	8.4	1.5	8.4	6	8400KG-10MM-RMA-RCH-1,5M	23.4
241326941102	8717365155086	10	8.4	2	8.4	6	8400KG-10MM-RMA-RCH-2M	28
2413269411025	8717365155093	10	8.4	2.5	8.4	6	8400KG-10MM-RMA-RCH-2,5M	32.6
241326941103	8717365155109	10	8.4	3	8.4	6	8400KG-10MM-RMA-RCH-3M	37.2
2413269411035	8717365155116	10	8.4	3.5	8.4	6	8400KG-10MM-RMA-RCH-3,5M	41.8
241326941104	8717365155123	10	8.4	4	8.4	6	8400KG-10MM-RMA-RCH-4M	46.4
241326941131	8717365155130	13	14	1	14	10,05	14T-13MM-RMA-RCH-1M	30.2
2413269411315	8717365155147	13	14	1.5	14	10,05	14T-13MM-RMA-RCH-1,5M	38.2
241326941132	8717365155154	13	14	2	14	10,05	14T-13MM-RMA-RCH-2M	46.2
2413269411325	8717365155161	13	14	2.5	14	10,05	14T-13MM-RMA-RCH-2,5M	54.2
241326941133	8717365155178	13	14	3	14	10,05	14T-13MM-RMA-RCH-3M	62.2
2413269411335	8717365155185	13	14	3.5	14	10,05	14T-13MM-RMA-RCH-3,5M	70.2
241326941134	8717365155192	13	14	4	14	10,05	14T-13MM-RMA-RCH-4M	78.2
241326941161	8717365155208	16	21	1	21	15	21T-16MM-RMA-RCH-1M	56.5
2413269411615	8717365155215	16	21	1.5	21	15	21T-16MM-RMA-RCH-1,5M	68.5
241326941162	8717365155222	16	21	2	21	15	21T-16MM-RMA-RCH-2M	80.5

Chain sling assy 4-leg REMA-10-RMA-RCX-RCH

Technical data

Part code	GTIN No.	Diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
2413269411625	8717365155239	16	21	2.5	21	15	21T-16MM-RMA-RCH-2,5M	92.5
241326941163	8717365155246	16	21	3	21	15	21T-16MM-RMA-RCH-3M	104.5
2413269411635	8717365155253	16	21	3.5	21	15	21T-16MM-RMA-RCH-3,5M	116.5
241326941164	8717365155260	16	21	4	21	15	21T-16MM-RMA-RCH-4M	128.5