

Chain sling assy 4-leg REMA-10-RMA-RCX-RCS

Product information



REMA[®]

The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

4 leg REMA-10 chain | masterlink RMA | connecting link RCX | self locking clevis hook RCS



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 17115, DIN 5692

Safety factor: 4

Grade: 10

Chain sling assy 4-leg REMA-10-RMA-RCX-RCS

Technical data

Part code	GTIN No.	Diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
241326942061	8717365155277	6	2.94	1	2.94	2,1	2940KG-6MM-RMA-RCS-1M	7
2413269420615	8717365155284	6	2.94	1.5	2.94	2,1	2940KG-6MM-RMA-RCS-1,5M	8.6
241326942062	8717365155291	6	2.94	2	2.94	2,1	2940KG-6MM-RMA-RCS-2M	10.2
2413269420625	8717365155307	6	2.94	2.5	2.94	2,1	2940KG-6MM-RMA-RCS-2,5M	11.8
241326942063	8717365155314	6	2.94	3	2.94	2,1	2940KG-6MM-RMA-RCS-3M	13.4
2413269420635	8717365155321	6	2.94	3.5	2.94	2,1	2940KG-6MM-RMA-RCS-3,5M	15
241326942064	8717365155338	6	2.94	4	2.94	2,1	2940KG-6MM-RMA-RCS-4M	16.6
241326942081	8717365155345	8	5.25	1	5.25	3,75	5250KG-8MM-RMA-RCS-1M	12.4
2413269420815	8717365155352	8	5.25	1.5	5.25	3,75	5250KG-8MM-RMA-RCS-1,5M	15.4
241326942082	8717365155369	8	5.25	2	5.25	3,75	5250KG-8MM-RMA-RCS-2M	18.4
2413269420825	8717365155376	8	5.25	2.5	5.25	3,75	5250KG-8MM-RMA-RCS-2,5M	21.4
241326942083	8717365155383	8	5.25	3	5.25	3,75	5250KG-8MM-RMA-RCS-3M	24.4
2413269420835	8717365155390	8	5.25	3.5	5.25	3,75	5250KG-8MM-RMA-RCS-3,5M	27.4
241326942084	8717365155406	8	5.25	4	5.25	3,75	5250KG-8MM-RMA-RCS-4M	30.4
241326942101	8717365155413	10	8.4	1	8.4	6	8400KG-10MM-RMA-RCS-1M	19.6
2413269421015	8717365155420	10	8.4	1.5	8.4	6	8400KG-10MM-RMA-RCS-1,5M	24.2
241326942102	8717365155437	10	8.4	2	8.4	6	8400KG-10MM-RMA-RCS-2M	28.8
2413269421025	8717365155444	10	8.4	2.5	8.4	6	8400KG-10MM-RMA-RCS-2,5M	33.4
241326942103	8717365155451	10	8.4	3	8.4	6	8400KG-10MM-RMA-RCS-3M	38
2413269421035	8717365155468	10	8.4	3.5	8.4	6	8400KG-10MM-RMA-RCS-3,5M	42.6
241326942104	8717365155475	10	8.4	4	8.4	6	8400KG-10MM-RMA-RCS-4M	47.2
241326942131	8717365155482	13	14	1	14	10,05	14T-13MM-RMA-RCS-1M	37
2413269421315	8717365155499	13	14	1.5	14	10,05	14T-13MM-RMA-RCS-1,5M	45
241326942132	8717365155505	13	14	2	14	10,05	14T-13MM-RMA-RCS-2M	53
2413269421325	8717365155512	13	14	2.5	14	10,05	14T-13MM-RMA-RCS-2,5M	61
241326942133	8717365155529	13	14	3	14	10,05	14T-13MM-RMA-RCS-3M	69
2413269421335	8717365155536	13	14	3.5	14	10,05	14T-13MM-RMA-RCS-3,5M	77
241326942134	8717365155543	13	14	4	14	10,05	14T-13MM-RMA-RCS-4M	85
241326942161	8717365155550	16	21	1	21	15	21T-16MM-RMA-RCS-1M	63.3
2413269421615	8717365155567	16	21	1.5	21	15	21T-16MM-RMA-RCS-1,5M	75.3
241326942162	8717365155574	16	21	2	21	15	21T-16MM-RMA-RCS-2M	87.3

Chain sling assy 4-leg REMA-10-RMA-RCX-RCS

Technical data

Part code	GTIN No.	Diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
2413269421625	8717365155581	16	21	2.5	21	15	21T-16MM-RMA-RCS-2,5M	99.3
241326942163	8717365155598	16	21	3	21	15	21T-16MM-RMA-RCS-3M	111.3
2413269421635	8717365155604	16	21	3.5	21	15	21T-16MM-RMA-RCS-3,5M	123.3
241326942164	8717365155611	16	21	4	21	15	21T-16MM-RMA-RCS-4M	135.3