

Chain sling assy 4-leg REMA-10-RMA-RDG-RCH

Product information



REMA[®]

The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

4-leg REMA-10 chain | masterlink RML | clevis shortening hook RDG | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 17115, DIN 5692

Safety factor: 4

Grade: 10

Chain sling assy 4-leg REMA-10-RMA-RDG-RCH

Technical data

Part code	GTIN No.	Diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
R2694306-1	8717365155628	6	2.94	1	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-1M	7.4
R2694306-1.5	8717365155635	6	2.94	1.5	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-1,5M	9
R2694306-2	8717365155642	6	2.94	2	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-2M	10.6
R2694306-2.5	8717365155659	6	2.94	2.5	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-2,5M	12.2
R2694306-3	8717365155666	6	2.94	3	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-3M	13.8
R2694306-3.5	8717365155673	6	2.94	3.5	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-3,5M	15.4
R2694306-4	8717365155680	6	2.94	4	2.94	2,1	2940KG-6MM-RMA-RDG-RCH-4M	17
R2694308-1	8717365155697	8	5.25	1	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-1M	14.4
R2694308-1.5	8717365155703	8	5.25	1.5	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-1,5M	17.4
R2694308-2	8717365155710	8	5.25	2	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-2M	20.4
R2694308-2.5	8717365155727	8	5.25	2.5	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-2,5M	23.4
R2694308-3	8717365155734	8	5.25	3	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-3M	26.4
R2694308-3.5	8717365155741	8	5.25	3.5	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-3,5M	29.4
R2694308-4	8717365155758	8	5.25	4	5.25	3,75	5250KG-8MM-RMA-RDG-RCH-4M	32.4
R2694310-1	8717365155765	10	8.4	1	8.4	6	8400KG-10MM-RMA-RDG-RCH-1M	24
R2694310-1.5	8717365155772	10	8.4	1.5	8.4	6	8400KG-10MM-RMA-RDG-RCH-1,5M	28.6
R2694310-2	8717365155789	10	8.4	2	8.4	6	8400KG-10MM-RMA-RDG-RCH-2M	33.2
R2694310-2.5	8717365155796	10	8.4	2.5	8.4	6	8400KG-10MM-RMA-RDG-RCH-2,5M	37.8
R2694310-3	8717365155802	10	8.4	3	8.4	6	8400KG-10MM-RMA-RDG-RCH-3M	42.4
R2694310-3.5	8717365155819	10	8.4	3.5	8.4	6	8400KG-10MM-RMA-RDG-RCH-3,5M	46
R2694310-4	8717365155826	10	8.4	4	8.4	6	8400KG-10MM-RMA-RDG-RCH-4M	51.6
R2694313-1	8717365155833	13	14	1	14	10,05	14T-13MM-RMA-RDG-RCH-1M	39.4
R2694313-1.5	8717365155840	13	14	1.5	14	10,05	14T-13MM-RMA-RDG-RCH-1,5M	47.4
R2694313-2	8717365155857	13	14	2	14	10,05	14T-13MM-RMA-RDG-RCH-2M	55.4
R2694313-2.5	8717365155864	13	14	2.5	14	10,05	14T-13MM-RMA-RDG-RCH-2,5M	63.4
R2694313-3	8717365155871	13	14	3	14	10,05	14T-13MM-RMA-RDG-RCH-3M	71.4
R2694313-3.5	8717365155888	13	14	3.5	14	10,05	14T-13MM-RMA-RDG-RCH-3,5M	79.4
R2694313-4	8717365155895	13	14	4	14	10,05	14T-13MM-RMA-RDG-RCH-4M	87.4
R2694316-1	8717365155901	16	21	1	21	15	21T-16MM-RMA-RDG-RCH-1M	72.9
R2694316-1.5	8717365155918	16	21	1.5	21	15	21T-16MM-RMA-RDG-RCH-1,5M	84.9
R2694316-2	8717365155925	16	21	2	21	15	21T-16MM-RMA-RDG-RCH-2M	96.9

Chain sling assy 4-leg REMA-10-RMA-RDG-RCH

Technical data

Part code	GTIN No.	Diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
R2694316-2.5	8717365155932	16	21	2.5	21	15	21T-16MM-RMA-RDG-RCH-2,5M	108.9
R2694316-3	8717365155949	16	21	3	21	15	21T-16MM-RMA-RDG-RCH-3M	120.9
R2694316-3.5	8717365155956	16	21	3.5	21	15	21T-16MM-RMA-RDG-RCH-3,5M	122.9
R2694316-4	8717365155963	16	21	4	21	15	21T-16MM-RMA-RDG-RCH-4M	136.9