

Chain sling assy 4-leg REMA-10-RMA-RDG-RCS

Product information



REMA[®]

The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

4 leg REMA-10 chain | masterlink RMA | clevis shortening hook RDG | self locking clevis hook RCS



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 17115, DIN 5692

Safety factor: 4

Grade: 10

Chain sling assy 4-leg REMA-10-RMA-RDG-RCS

Technical data

Part code	GTIN No.	Diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
241326944061	8717365155970	6	2.94	1	2.94	2,1	2940KG-6MM-RMA-RDG-RCS-1M	8.2
2413269440615	8717365155987	6	2.94	1.5	2.94	2,1	2940KG-6MM-RMA-RDG-RCS-1,5M	9.8
241326944062	8717365155994	6	2.94	2	2.94	2,1	2940KG-6MM-RMA-RDG-RCS-2M	11.4
2413269440625	8717365156007	6	2.94	2.5	2.94	2,1	2940KG-6MM-RMA-RDG-RCS-2,5M	13
241326944063	8717365156014	6	2.94	3	2.94	2,1	2940KG-6MM-RMA-RDG-RCS-3M	14.6
2413269440635	8717365156021	6	2.94	3.5	2.94	2,1	2940KG-6MM-RMA-RDG-RCS-3,5M	16.2
241326944064	8717365156038	6	2.94	4	2.94	2,1	2940KG-6MM-RMA-RDG-RCS-4M	17.8
241326944081	8717365156045	8	5.25	1	5.25	3,75	5250KG-8MM-RMA-RDG-RCS-1M	14.8
2413269440815	8717365156052	8	5.25	1.5	5.25	3,75	5250KG-8MM-RMA-RDG-RCS-1,5M	17.8
241326944082	8717365156069	8	5.25	2	5.25	3,75	5250KG-8MM-RMA-RDG-RCS-2M	20.8
2413269440825	8717365156076	8	5.25	2.5	5.25	3,75	5250KG-8MM-RMA-RDG-RCS-2,5M	23.8
241326944083	8717365156083	8	5.25	3	5.25	3,75	5250KG-8MM-RMA-RDG-RCS-3M	26.8
2413269440835	8717365156090	8	5.25	3.5	5.25	3,75	5250KG-8MM-RMA-RDG-RCS-3,5M	29.8
241326944084	8717365156106	8	5.25	4	5.25	3,75	5250KG-8MM-RMA-RDG-RCS-4M	32.8
241326944101	8717365156113	10	8.4	1	8.4	6	8400KG-10MM-RMA-RDG-RCS-1M	24.8
2413269441015	8717365156120	10	8.4	1.5	8.4	6	8400KG-10MM-RMA-RDG-RCS-1,5M	29.4
241326944102	8717365156137	10	8.4	2	8.4	6	8400KG-10MM-RMA-RDG-RCS-2M	34
2413269441025	8717365156144	10	8.4	2.5	8.4	6	8400KG-10MM-RMA-RDG-RCS-2,5M	38.6
241326944103	8717365156151	10	8.4	3	8.4	6	8400KG-10MM-RMA-RDG-RCS-3M	43.2
2413269441035	8717365156168	10	8.4	3.5	8.4	6	8400KG-10MM-RMA-RDG-RCS-3,5M	47.8
241326944104	8717365156175	10	8.4	4	8.4	6	8400KG-10MM-RMA-RDG-RCS-4M	52.4
241326944131	8717365156182	13	14	1	14	10,05	14T-13MM-RMA-RDG-RCS-1M	46.2
2413269441315	8717365156199	13	14	1.5	14	10,05	14T-13MM-RMA-RDG-RCS-1,5M	54.2
241326944132	8717365156205	13	14	2	14	10,05	14T-13MM-RMA-RDG-RCS-2M	62.2
2413269441325	8717365156212	13	14	2.5	14	10,05	14T-13MM-RMA-RDG-RCS-2,5M	70.2
241326944133	8717365156229	13	14	3	14	10,05	14T-13MM-RMA-RDG-RCS-3M	78.2
2413269441335	8717365156236	13	14	3.5	14	10,05	14T-13MM-RMA-RDG-RCS-3,5M	86.2
241326944134	8717365156243	13	14	4	14	10,05	14T-13MM-RMA-RDG-RCS-4M	94.2
241326944161	8717365156250	16	21	1	21	15	21T-16MM-RMA-RDG-RCS-1M	79.7
2413269441615	8717365156267	16	21	1.5	21	15	21T-16MM-RMA-RDG-RCS-1,5M	91.7
241326944162	8717365156274	16	21	2	21	15	21T-16MM-RMA-RDG-RCS-2M	103.7

Chain sling assy 4-leg REMA-10-RMA-RDG-RCS

Technical data

Part code	GTIN No.	Diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Model	Weight kg
2413269441625	8717365156281	16	21	2.5	21	15	21T-16MM-RMA-RDG-RCS-2,5M	115.7
241326944163	8717365156298	16	21	3	21	15	21T-16MM-RMA-RDG-RCS-3M	127.7
2413269441635	8717365156304	16	21	3.5	21	15	21T-16MM-RMA-RDG-RCS-3,5M	139.7
241326944164	8717365156311	16	21	4	21	15	21T-16MM-RMA-RDG-RCS-4M	151.7