CERTEX | Lifting Solutions Group
Axel Johnson International

RC stainless steel chain AISI 316 (G6)

Product information



CARTEC

Grade 6 Stainless Steel Chain Slings and components are meticulously crafted using top-tier stainless steel (AISI 316), our slings are not just durable but also versatile. With the availability of individual components, we ensure a sustainable and customizable solution tailored to your specific lifting requirements. Our stainless steel assemblies are trusted across a myriad of industries such as construction, food & beverage, healthcare, aerospace, marine, and beyond.

Utilization Features:

1. **Durability:** Made with premium AISI 316 stainless steel, ensuring longevity and resistance to corrosion.
2. **Versatility:** Suitable for a range of lifting operations with various assembly options.
3. **Safety:** Comes with a CE-mark and a safety factor of 4, ensuring utmost safety during operations.
4. **Adaptability:** Individual component availability for a tailored lifting solution.

Markets/Applications:

- **Construction:** Ideal for heavy-duty lifting and construction site operations.
- **Food & Beverage:** Stainless steel ensures hygiene and cleanliness, making it perfect for food-related lifting tasks.
- **Medical:** Suitable for lifting medical equipment and supplies.
- **Aerospace:** Can be used for lifting aerospace components.
- **Marine:** Resistant to corrosion, making it perfect for marine applications

... Read more

Material: AISI 316
Marking: According to standard, CE-mark
Standard: EN 818-4


Safety factor: 4
Grade: 6

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

RC stainless steel chain AISI 316 (G6)

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	Model	B1 mm	B2 mm	D mm	T mm	Weight kg/m
202100600000030	6	0.9	RC 6 X 18 MM	8	22.2	6	18	0.58
202100700000030	7	1.25	RC 7 X 21 MM	9.1	25.9	7	21	1.11
202100800000030	8	1.6	RC 8 X 24 MM	10.4	29.6	8	24	1.68
202101000000030	10	2.5	RC 10 X 30 MM	14	37	10	30	3.77
202101300000030	13	4.25	RC 13 X 39 MM	16.9	48.1	13	39	5.62

© November 2026 - All Rights Reserved