



C807X+KEY lifting points (Grade 10)

Product information

CARTEC

Features: Tighten hand-tight in load direction.

Marking: According to standard, CE-marked

Standard: EN 1677-1

Note: Rotatable through 360°

Warning: Not rotatable under load.

Safety factor: 4

Grade: 10

| Part code | Code | WLL ton | Thread mm | Model | A mm | B mm | C mm | D, mm | E mm | F mm | K mm | M x Lmm mm | SWlmm mm | Weight kg | Delivery time |
|-----------|---------------|---------|-----------|------------------------|------|------|------|-------|------|-------|------|------------|----------|-----------|---------------|
| R2611408 | 8717365116018 | 0.3 | M8 | C807X+KEY-M8x12-0.3T | 35 | 11 | 9 | 25 | 25 | 30 | 47 | M8 x 12 | 6 | 0.12 | 3 |
| R2611410 | 8717365116025 | 0.4 | M10 | C807X+kKEY-M10x15-0.4T | 35 | 11 | 9 | 25 | 25 | 30 | 47 | M10 x 16 | 6 | 0.12 | 3 |
| R2611412 | 8717365116032 | 0.75 | M12 | C807X+KEY-M12x23-0.75T | 43 | 12,5 | 11,5 | 30 | 30 | 36,5 | 55,5 | M12 x 18 | 7 | 0.2 | 3 |
| R2611416 | 8717365116049 | 1.5 | M16 | C807X+KEY-M16x24-1.5T | 49,5 | 14,5 | 15,7 | 35 | 35 | 41,8 | 64,5 | M16 x 24 | 8 | 0.35 | 3 |
| R2611420 | 8717365116056 | 2.3 | M20 | C807X+KEY-M20x30-2.3T | 58 | 16 | 18 | 40 | 42 | 51,5 | 74,5 | M20 x 30 | 10 | 6 | 3 |
| R2611424 | 8717365116063 | 3.2 | M24 | C807X+KEY-M24x36-3.2T | 69 | 20,5 | 22 | 49 | 50 | 58 | 90 | M24 x 36 | 12 | 1 | 3 |
| R2611430 | 8717365116070 | 4.5 | M30 | C807X+KEY-M30x45-4.5T | 86 | 25,5 | 28 | 60 | 66 | 73 | 111 | M30 x 43 | 17 | 2 | 3 |
| R2611436 | 8717365116087 | 7 | M36 | C807X+KEY-M36x54-7.0T | 107 | 32 | 32 | 74 | 75 | 96,5 | 135 | M36 x 54 | 22 | 2 | 30 |
| R2611442 | 8717365116094 | 9 | M42 | C807X+KEY-M42x63-9.0T | 120 | 38 | 40,5 | 82 | 85 | 110 | 158 | M42 x 64 | 24 | 5.7 | 30 |
| R2611448 | 8717365116100 | 12 | M48 | C807X+KEY-M48x72-12T | 139 | 43 | 44 | 95 | 100 | 124,5 | 179 | M48 x 72 | 27 | 8.5 | 30 |

Blueprint

