

Eye-bolt (DIN-580)

Product information



High-alloyed steel eyebolt. Eye bolts may only be tightened by hand.
Safe workload, under a maximum angle of 60° as shown.
The lifting eye must not be loaded sideways.

... [Read more](#)

Marking: According to standard, CE-marked

Standard: EN 1677-1, DIN 580

Safety factor: 4

Grade: 8

Eye-bolt (DIN-580)

Technical data

Part code	Code	WLL ton	Thread mm	Model	A mm	B mm	C mm	D mm	M mm	Weight kg
421100040480	8717365115202	0.4	M8	DIN580-G8-M8	34	7	20	13	M8 x 1,25	0.05
421100070480	8717365115219	0.7	M10	DIN580-G8-M10	38	8	22	17	M10 x 1,50	0.07
421100100480	8717365115226	1	M12	DIN580-G8-M12	47	10	26	21	M12 x 1.75	0.13
421100150480	8717365115233	1.5	M16	DIN580-G8-M16	64	14	35	27	M16 x 2.00	0.34
421100250480	8717365115240	2.5	M20	DIN580-G8-M20	73	16	39	30	M20 x 2.50	0.52
421100400480	8717365115257	4	M24	DIN580-G8-M24	95	20	54	36	M24 x 3.00	0.99