CERTEX | Lifting Solutions Group
Axel Johnson International

CBU Lightweight Holland profile (Hp) clamp for universal lifting

Product information



REMA®

Specifically developed for lifting and transportation HP profiles and ship constructions using HP profiles. Fitted with 2 cams and universal lifting eyes.

Application

- For vertical lifting, handling and transporting of Holland Profile (HP) shipbuilding structures from all positions
- Jaw openings available from: 0 to 45 mm
- Higher WLL available upon request.
- Lifting of longer sections should be performed with a spreader beam fitted with multiple clamps.

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 13155, EN 12100
Warning: Min . WLL is 10% of max . WLL.


Safety factor: 5

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

CBU Lightweight Holland profile (Hp) clamp for universal lifting

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	Weight kg
50213310001	8717365015083	3	0-35	CBU-3.0	90	70	370	185	55	54	8
50213310003	8717365015090	5	0-45	CBU-5.0	110	70	435	225	60	86	17.3

© November 2026 - All Rights Reserved