



WF-screw clamp

Product information



WF screw clamps are the lightest clamps with the highest capacity by means of a double round pivot. Special high-quality Alloy steel housing provides a safety factor of 8. The clamp is equipped with a double locking mechanism with movable pivots that guarantees increased clamping capacity.

Properties

- Double round pivot locking, resulting in stronger clamping force and safe operation.
- Because of the two attachment holes it is possible to carry out work in all directions.
- This clamp can be used to hoist inclined loads such as I-beams.
- Fine adjusting screw thread.
- Preservation powder coating.
- The pivots and the screw are specially treated to prevent rusting.

Application

- Hoisting and transport work: Steel material, including H-beams, I-beams, steel plates, tubes, angle profiles and steel posts, as well as steel beams, pillars, welded objects and other workpieces.
- Lowering workpieces easily with any hoisting equipment.
- Dragging steel plates to arrange them on the ground.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13155

Part code	GTIN No.	WLL ton	Jaw width mm	Model	Minimum load kg	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	L mm	M mm	N mm	O mm	P mm	Q mm	R mm	Weight kg	Delivery time
R3316001	8717365030727	0.5	3-28	WF-0.5	50	41	32	30.5	21	33	108	138	34	42	10	25	24.5	12	16	120	10	26	21	1.5	3
R3316003	8717365030734	1	3-40	WF-1.0	100	53.5	38	42.5	25	40	132	172	34	50	10	30	29.5	16	20	120	12	34	26	2.9	3
R3316005	8717365030741	2	3-45	WF-2.0	200	60	45	47.5	31	41	157	202	34	62	10	34	33	22	28	150	12	36	29	4.9	3
R3316007	8717365030758	3	6-49	WF-3.0	300	65.5	52	51.5	35	44	170	230	34	70	10	35	40.5	28	33	160	12	40	36	7.2	3
R3316009	8717365030765	5	9-53	WF-5.0	500	71	57	55.5	38	46	187	248	34	75	10	40	45	38	40	180	12	41	36	10	3

Blueprint

