



CS vertical plate lifting clamps

Product information



Lifting clamps for safely transporting steel plates in vertical position.

Properties

- Equipped with standard lifting eye, movable in one direction.
- Always equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when load is being lowered.
- WLL and size of the jaw opening are clearly indicated on the clamp.
- Safety factor of at least 5 x WLL.
- Each clamp is 2x WLL testloaded.

Application

- For lifting steel plates up to a hardness of 37 RC (345 HB).
- Suitable for lifting, 180 ° turning and vertical transport of steel plates.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13155

Note: Minimum weight to be lifted is 10% of the safe workload.

Safety factor: 5

| Part code | GTIN No. | WLL ton | Jaw width mm | Model | A, | B, | C, | D, | E, | F, | G, | Weight kg | Delivery time |
|-----------|---------------|---------|--------------|---------|-----|----|-----|-----|-----|-----|----|-----------|---------------|
| R3360001 | 8717365015595 | 0.75 | 0-13 | CS-0.75 | 47 | 30 | 205 | 100 | 35 | 37 | 10 | 1.5 | 3 |
| R3360002 | 8717365261862 | 1 | 0-25 | CSE-1.0 | 55 | 45 | 265 | 142 | 38 | 47 | 15 | 3.6 | 3 |
| R3361002 | 8717365015625 | 2 | 0-35 | CS-2.0 | 80 | 65 | 335 | 185 | 55 | 56 | 17 | 6.5 | 3 |
| R3361003 | 8717365015632 | 3 | 0-35 | CS-3.0 | 80 | 65 | 335 | 185 | 55 | 56 | 17 | 7 | 3 |
| R3361004 | 8717365015649 | 4 | 0-45 | CS-4.0 | 85 | 70 | 430 | 230 | 60 | 78 | 20 | 16 | 3 |
| R3361006 | 8717365015656 | 6 | 0-50 | CS-6.0 | 114 | 75 | 490 | 255 | 78 | 78 | 20 | 20 | 3 |
| R3361009 | 8717365015663 | 9 | 0-55 | CS-9.0 | 112 | 75 | 530 | 267 | 70 | 86 | 20 | 26 | 3 |
| R3361013 | 8717365015670 | 12 | 0-52 | CS-12.0 | 148 | 85 | 617 | 295 | 100 | 94 | 44 | 42 | 30 |
| R3361015 | 8717365015687 | 15 | 0-75 | CS-15.0 | 159 | 86 | 760 | 375 | 135 | 105 | 50 | 71 | 30 |

Blueprint

