CERTEX | Lifting Solutions Group
Axel Johnson International

CU universal plate lifting clamps

Product information



REMA®

Lifting clamps for safely transporting steel plates in vertical position.

Properties

- Equipped with universal lifting eye, movable in two directions.
- Always equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when load is being lowered.
- WLL and size of the jaw opening are clearly indicated on the clamp.
- Safety factor of at least 5 x WLL.
- Each clamp is 2x WLL testloaded.

Application

- For lifting steel plates up to a hardness of 37 RC (345 HB).
- Suitable for lifting, 180 ° turning and vertical transport of steel plates

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 13155, EN 12100
Note: Minimum weight to be lifted is 10% of the safe workload.

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

CU universal plate lifting clamps

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg
50213362001	8717365015694	0.75	0-13	CU-0.75	47	30	203	100	35	37	10	1.7
50213362002	8717365261879	1	0-25	CUE-1.0	55	50	295	125	38	47	14	3.9
50213363002	8717365015724	2	0-35	CU-2.0	80	70	370	185	55	56	16	7.3
50213363003	8717365020391	3	0-35	CU-3.0	80	70	370	185	55	56	16	8
50213363004	8717365015731	4	0-45	CU-4.0	85	70	430	230	60	78	20	17
50213363006	8717365015748	6	0-50	CU-6.0	114	78	527	255	78	78	32	22
50213363009	8717365015755	9	0-55	CU-9.0	112	78	565	267	70	86	45	30
50213363013	8717365015762	12	0-52	CU-12.0	148	85	650	295	100	94	48	44
50213363015	8717365015779	15	0-76	CU-15.0	159	85	765	373	136	106	48	75

© November 2026 - All Rights Reserved