

CU-H universal plate lifting clamps for plates till 50RC (485 HB)

Product information

**REMA**[®]

Lifting clamps for safely transporting steel plates in vertical position.

Properties

- Equipped with universal lifting eye, movable in two directions.
- Always equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when load is being lowered.
- WLL and size of the jaw opening are clearly indicated on the clamp.
- Safety factor of at least 5 x WLL.
- Each clamp is 2x WLL testloaded.

Application

- For lifting steel plates up to a hardness of 50 RC (485 HB).
- Suitable for lifting, 180 ° turning and vertical transport of steel plates

[... Read more](#)

Marking: According to standard, CE-marked


Standard: EN 12100, EN 13155

Note: Minimum weight to be lifted is 10% of the safe workload.

Safety factor: 5

CU-H universal plate lifting clamps for plates till 50RC (485 HB)

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	G, mm	Weight kg
R3363101	8717365024719	0.75	0-13	CU-0.75H	47	30	203	100	35	37	10	1.7
R3363103	8717365024726	1	0-25	CU-1.0H	55	50	295	142	38	47	14	3.9
R3363105	8717365024733	2	0-35	CU-2.0H	80	70	370	185	55	56	16	7.3
R3363107	8717365024740	3	0-35	CU-3.0H	80	70	370	185	55	56	16	8
R3363109	8717365024757	4	0-45	CU-4.5H	85	70	430	230	60	78	20	17
R3363111	8717365024764	6	0-32	CU-6.0H	114	78	528	225	78	78	32	22