KSB spindle beam clamps

Product information



REMA®

For safe lifting and moving of steel beams or as a fixed suspension point.

Properties

- Low constructional height.
- Easy mounting due to the spindle.
- Suitable for both IPE or INP steel beams.

... *Read more*

Marking: CE-mark


Safety factor: 4

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

KSB spindle beam clamps

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Beam width mm	Model	A max mm	B max mm	B min mm	C mm	D mm	E mm	F max mm	F min mm	G mm	H mm	J mm	Weight kg
50233317001	8717365015540	1	80-240	KSB-1	270	370	183	94	4	198	154	100	22	20	20	3.5
50233317002	8717365015557	2	80-240	KSB-2	270	370	183	102	6	198	154	100	22	20	20	4.5
50233317003	8717365015564	3	90-330	KSB-3	355	500	243	132	8	263	219	148	46	22	38	9.5
50233317005	8717365015571	5	90-330	KSB-5	355	500	243	142	10	263	219	148	43	28	38	11
50233317010	8717365015588	10	90-350	KSB-10	364	521	269	180	12	285	239	165	51	38	38	18

© November 2026 - All Rights Reserved