



Superclamp USC-serie

Product information



Adjustable beam clamps for rail profiles.

Properties

- Fitted with a special catch to prevent beams from displacement.
- With fixed suspension eyes allowing loads at any angles.

Application:

- To be use as a semi-permanent suspension point at angle beams.

Marking: According to standard, CE-marked

Standard: EN 13157, EN 12100

| Part code | GTIN No. | WLL ton | Beam width mm | Jaw width mm | Model | A mm | B mm | C mm | D mm | E mm | G mm | H mm | J mm | Weight kg | Delivery time |
|-----------|---------------|---------|---------------|--------------|-------|------|------|------|------|------|------|------|------|-----------|---------------|
| R3507007 | 8717365016974 | 3 | 125-204 | | USC3A | 387 | - | 70 | 48 | 32 | 100 | 25.4 | 28 | 13.5 | 3 |
| R3507009 | 8717365016981 | 4 | 125-305 | | USC4 | 518 | 10 | 70 | 48 | 32 | 100 | 25.4 | 28 | 23.5 | 3 |
| R3507011 | 8717365016998 | 5 | 125-305 | | USC5 | 524 | 10 | 75 | 48 | 32 | 120 | 25.4 | 38 | 28.5 | 3 |

Blueprint

