



## HSD double scissor stationary lifting table

### Product information



The table can be mounted both on the floor and in the floor.

#### Properties

- This lifting table is equipped with an aluminium safety frame.
- Overload protection.
- Solid steel scissors.
- Special valve for controlled descent.
- Hose rupture safety valve.
- Lifetime lubricated bearings.
- Operating voltage 400V, control voltage 24V.
- Protection class IP54.

Hard chromed cylinder and piston rod.

#### Standard delivery

- Includes 24 V push button switch with emergency stop.
- Removable lifting eyes for easy transport.

**Marking:** According to standard, CE-marked

**Standard:** EN 12100, EN 13157

| Part code | GTIN No.      | WLL ton | Model   | Lifting times | Motor kW | Lifting cycle/hour | A mm | B mm  | C mm  | D, mm | E mm  | H, mm | Weight kg | Delivery time |
|-----------|---------------|---------|---------|---------------|----------|--------------------|------|-------|-------|-------|-------|-------|-----------|---------------|
| R3459031  | 8717365021831 | 1       | HSD-1.0 | 35            | 2.2      | 12                 | 348  | 1,300 | 820   | 680   | 1,266 | 1,823 | 210       | 3             |
| R3459033  | 8717365021848 | 2       | HSD-2.0 | 35            | 2.2      | 12                 | 403  | 1,300 | 850   | 785   | 1,255 | 1,823 | 295       | 3             |
| R3459035  | 8717365021855 | 4       | HSD-4.0 | 55            | 2.2      | 8                  | 448  | 1,700 | 1,200 | 930   | 1,600 | 2,098 | 520       | 3             |

# Blueprint

