

HSD double scissor stationary lifting table

Product information



The table can be mounted both on the floor and in the floor.

Properties

- This lifting table is equipped with an aluminium safety frame.
- Overload protection.
- Solid steel scissors.
- Special valve for controlled descent.
- Hose rupture safety valve.
- Lifetime lubricated bearings.
- Operating voltage 400V, control voltage 24V.
- Protection class IP54.

Hard chromed cylinder and piston rod.

Standard delivery


- Includes 24 V push button switch with emergency stop.
- Removable lifting eyes for easy transport.

[... Read more](#)

Marking: According to standard, CE-marked
Standard: EN 12100, EN 13157

HSD double scissor stationary lifting table

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Model	Lifting times	Motor kW	Lifting cycle/hour	A mm	B mm	C mm	D mm	E mm	H mm	Weight kg
90213459031	8717365021831	1	HSD-1.0	35	2.2	12	348	1,300	820	680	1,266	1,823	210
90213459033	8717365021848	2	HSD-2.0	35	2.2	12	403	1,300	850	785	1,255	1,823	295
90213459035	8717365021855	4	HSD-4.0	55	2.2	8	448	1,700	1,200	930	1,600	2,098	520