

## HS stationary lifting tables

### Product information

**REMA**<sup>®</sup>

The universal stationary lifting table for lifting heavy loads can be used in a space-saving manner by placing the lifting table in a pit.

#### Properties

- Robust supportconstruction.
- Profile reinforced table.
- Solid steel scissors.
- This lifting table is equipped with an aluminium safety frame.
- Support inspection for safe maintenance.
- Overload protection.
- Hose rupture safety valve.
- Hard chromed cylinder and piston rod.
- Lifetime lubricated bearings.
- Operating voltage 400V, control voltage 24V.
- Protection class IP54.

#### Standard delivery

- Includes 24 V push button switch with emergency stop.
- Removable lifting eyes for easy transport.

**Marking:** According to standard, CE-marked

**Standard:** EN 12100, EN 1570



Part code	GTIN No.	WLL ton	Model	Lifting times	Motor kW	Lifting cycle/hour	A mm	B mm	C mm	D mm	E mm	H mm	Weight kg	Delivery time
R3459005	8717365021534	0.5	HS05-01	25	1.1	21	243	2,000	800	680	1,615	1,043	193	30
R3459001	8717365016257	1	HS1-01	20	0.75	21	248	1,300	820	640	1,240	1,033	160	3
R3459007	8717365021824	1	HS1-04	30	1.1	15	283	1,700	1,000	640	1,580	1,343	210	3
R3459002	8717365016264	2	HS2-01	20	1.5	21	273	1,300	850	785	1,220	1,043	235	3
R3459003	8717365021817	2	HS2-06	35	2.2	15	293	2,000	1,000	785	1,600	1,343	375	3
R3459004	8717365016271	4	HS4-01	40	2.2	13	288	1,700	1,200	900	1,600	1,098	375	3
R3459006	8717365021541	4	HS4-06	45	2.2	10	348	2,200	1,200	900	2,000	1,448	505	3

## Blueprint

