



HSU low profile lifting table

Product information



For lifting heavy loads in the simplest possible way, then the low U stationary lifting table offers a solution because this table has a recess where a pallet truck can be placed. The extremely low lifting table prevents time-consuming construction efforts for the creation of a pit.

Properties

- Stable low bottom plate.
- Solid steel scissors.
- This lifting table is equipped with an aluminium safety frame.
- Support inspection for safe maintenance.
- Overload protection.
- Hose rupture safety valve.
- Hard chromed cylinder and piston rod.
- Lifetime lubricated bearings.
- External drive unit.
- Operating voltage 400V, control voltage 24V.
- Protection class IP54.

Standard delivery

- Incl 24 V remote control buttons and emergency stop.
- Demountable lifting eyes for easy transport.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

| Part code | GTIN No. | WLL ton | Model | Lifting times | Motor kW | Lifting cycle/hour | A mm | B mm | C mm | D, mm | E mm | F mm | G, mm | H, mm | Weight kg | Delivery time |
|-----------|---------------|---------|---------|---------------|----------|--------------------|------|-------|-------|-------|-------|------|-------|-------|-----------|---------------|
| R3459017 | 8717365016318 | 1 | HSU-1.0 | 18 | 0.75 | 20 | 85 | 1,450 | 1,140 | 1,074 | 1,325 | 585 | 1,080 | 860 | 280 | 3 |
| R3459019 | 8717365016325 | 1.5 | HSU-1.5 | 18 | 1.5 | 20 | 105 | 1,600 | 1,180 | 1,114 | 1,427 | 585 | 1,194 | 860 | 380 | 3 |

Blueprint

