CERTEX | Lifting Solutions Group
Axel Johnson International

EWL electric worm gear winches (NOT FOR LIFTING)

Product information



REMA®

Price/quality ratio of series Rema® EWL electric self locking worm gear winches is very fair; they are available in designs complying with various classifications and norms.

Properties

- Pulling force: 250 kg to 2800 kg.
- Drums run on bearings at both sides (from model EWL 1000).
- Steel base plate (from model EWL 1000).

Standard delivery

- Does not include steel wire rope.
- Does not include control pendant.
- Above 1000 kg overload limiter is required.

Option

- Steel wire rope.
- Control pendant included switch box.
- Overload limiter (above 1000 kg required).
- Maritime design on special order.

... *Read more*

Marking: According to standard, CE-marked
Standard: EN 12100, EN 14492
Warning: Not suitable for lifting.

© October 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

EWL electric worm gear winches (NOT FOR LIFTING)

Technical data

Part code	GTIN No.	WLL ton	Model	Rope Ø mm	Max. reel capacity mm	Motor kW	WLL Pulling 1st layer kg	Speed 1st layer m/min	A mm	B mm	C mm	D1 mm	D2 mm	E mm	F mm	G mm	H mm	K mm	L mm	M mm	N mm	Weight kg
54062300001	8717365261220	0.25	EWL-250	6	20	0.55	250	8.4	405	284.6	306.6	190	101.6	6	117	60	114	120	250	139	158	21
54062300003	8717365261237	0.5	EWL-500	6	20	1.1	500	8.4	460	299	348	190	106.6	6	125	60	138	140	279	156	193	36
54062300005	8717365261244	0.75	EWL-750	6	20	1.1	750	5.8	460	299	348	190	106.6	6	125	60	138	140	279	156	193	36
54062300007	8717365261251	1	EWL-1000	8	40	1.5	1,000	6	589	540	436	250	101.6	6	215	150	500	275	264	130	325	90
54062300009	8717365261268	1.25	EWL-1250	8	40	2.2	1,250	6	589	540	436	250	101.6	6	215	150	500	275	282	158	325	93
54062300011	8717365261275	1.75	EWL-1750	10	53	3	1,750	5.8	660	640	474	280	121	8	262	200	600	320	307	190	370	136
54062300013	8717365261282	2.25	EWL-2250	12	65	4	2,250	7	706	710	524	320	146	8	300	250	670	360	307	190	410	192
54062300015	8717365261299	2.8	EWL-2800	14	75	5.5	2,800	7.8	825	850	607	370	159	8	333	300	800	380	324	216	440	302

Model	A mm	B mm	C mm	D1 mm	D2 mm	E mm	F mm	G mm	H mm	K mm	L mm	M mm	N mm
EWL-250	405	284,6	306,6	190	101,6	6	117	60	114	120	250	139	158
EWL-500	460	299	348	190	106,6	6	125	60	138	140	279	156	193
EWL-750	460	299											

© October 2026 - All Rights Reserved