CERTEX | Lifting Solutions Group
Axel Johnson International

TL Gear winch

Product information



REMA®

Properties

- Load pressure brake.
- Adjustable crank length; backwind-free.
- The drums and the shaft supported by needle bearings.
- Paint finish and enamel varnish are standard.
- Capacity min. 2%

Standard delivery:

- Does not include wire rope.

Option:

- Wire rope on request with hook and safety latch.

... *Read more*


Marking: According to standard, CE-mark
Standard: EN 13157, EN 12100

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

TL Gear winch

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Model	Rope Ø mm	WLL top layer ton	Lift/crank turn (mm)	Max. reel capacity mm	Hand force max. kg	Weight kg
50132015008	8717365273742	0.15	TL-0.150	4	0.068	122	13	11	4
50132015009	8717365008733	0.3	TL-0.3	5	0.12	21	25	7	10
50132015012	8717365273759	0.6	TL-0.6	6	0.232	28	12	10	11
50132015013	8717365008757	1	TL-1.0	10	0.684	21	28	15	28
50132015014	8717365273766	1.5	TL-1.5	14	0.844	14	21	12	27.5

Model	A	B	C	D	G	H	J	K	L	M	N	O	P	S
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
TL-0.150	65	168	128	40	6	40,5	35	9 (3x)	102	-	89	303	280	128,5
TL-0.3	200													

© November 2026 - All Rights Reserved