

Beam Clamp - IPBK10

Product information



The IPBK10 beam clamp is used for lifting, transferring and stacking HBeams. A ring-center hoist eye allows for the beam flange to remain vertical. This series of clamps can be used in vertical and horizontal moving, transferring and stacking of different types of structural designs, such as H-Beams, angles, etc, depending on the application desired.

Features:

- Available in capacities of 0.5 through 4 metric tons.
- Jaw openings available: 5 to 28mm
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- For use with materials with a plate surface hardness to 279HV10, only 5% min WLL is needed.
- All sizes are RFID EQUIPPED.

... [Read more](#)

Material: Alloy steel.

Marking: According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number


Temperature range: -40°C up to +100°C

Standard: EN 13155

Warning: A minimum load of 10% of the WLL is required.

Beam Clamp - IPBK10

Blueprint



Technical data

Part code	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	G, mm	H, mm	J mm	Weight kg
502100050150840	0.5	5-15	0.5-IPBK10	5-15	75	282	431	100	232	78	72	20	2.4
502100100150840	1	5-15	1-IPBK10	5-15	43	134	216	45	120	48	45	10	2.6
502100200250840	2	5-25	2-IPBK10	5-25	43	152	230	45	123	47	45	10	7.3
502100400280840	4	5-28	4-IPBK10	5-28	62	223	341	70	198	61	70	16	16.9