

## Fast Connector Socket FCS Spin Resistant - with pin



### Product information

Forged clevis fittings with pin and cutterpin for fast connection of steel wire rope. Connector shall be used with non-rotation resistant wire rope and may be used with rotation resistant wire rope.

The connector has to be moulded / casted on the steel wire rope with wirelock resin.

**Features:** Designed for use with mobile cranes.

**Material:** Quenched and tempered cast steel.

**Finish:** Blue painted (P) or hot dip galvanized (G).

**Warning:** Compare the spelter's and the wire rope's minimum breaking load.

Part code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	TB mm	TL mm	Weight kg	Delivery time
122102600292	FCS 705 P.SR	23-26	75	Galvanized	115	123	60	28	51	22	51	104	60	95	90	128	298	11	30
122102600295	FCS 705 P.SR	23-26	75	Painted	115	123	60	28	51	22	51	104	60	95	90	128	298	11	30
122102900292	FCS 706 P.SR	27-29	90	Galvanized	140	152	65	32	71	25	57	114	70	107	116	142	357	16	30
122102900295	FCS 706 P.SR	27-29	90	Painted	140	152	65	32	71	25	57	114	70	107	116	142	357	16	30
122103900292	FCS 709 P.SR	37-39	150	Galvanized	176	187	80	42	70	30	76	142	90	136	142	177	443	29	30
122103900295	FCS 709 P.SR	37-39	150	Painted	176	187	80	42	70	30	76	142	90	136	142	177	443	29	30
122104200295	FCS 710 P.SR	40-42	170	Painted	188	198	88	45	76	33	76	156	95	142	150	187	474	36	30
122104200292	FCS 710 P.SR	40-42	170	Galvanized	188	198	88	45	76	33	76	156	95	142	150	187	474	36	30
122104800295	FCS 711 P.SR	43-48	225	Painted	210	232	100	52	89	39	89	176	110	167	175	215	542	58	30
122104800292	FCS 711 P.SR	43-48	225	Galvanized	210	232	100	52	89	39	89	176	110	167	175	215	542	58	30

# Blueprint

