

## Super Shackle no 858, Gunnebo with safety Bolt

### Product information

Bow shackle with safety bolt.

... [Read more](#)



**Material:** High tensile steel, quenched and tempered

**Marking:** According to standard, CE-marked, WLL

**Temperature range:** -20°C up to 200°C

**Finish:** All parts hot dip galvanized + brown colour marking


**Standard:** US. FED. SPEC. RR-C-271

**Safety factor:** 5:1

**Grade:** 8

## Super Shackle no 858, Gunnebo with safety Bolt

### Blueprint



### Technical data

Part code	WLL ton	a mm	c mm	d mm	d1 mm	d2 mm	e mm	Weight kg
420100330480	3.3	21	51	1/2" - 13	16	33	33	0.4
420100500480	5	27	60	5/8" - 16	19	40	42	0.7
420100700480	7	31	71	3/4" - 19	22	48	49	1.2
420100950480	9.5	37	84	7/8" - 22	25	52	60	1.7
420101250480	12.5	43	95	1" - 25	28	60	68	2.5
420101500480	15	46	108	1 1/8" - 28	32	64	74	3.4
420101800480	18	52	119	1 1/4" - 32	35	72	83	4.8
420102100480	21	57	132	1 3/8" - 35	38	76	89	7
420103000480	30	60	146	1 1/2" - 38	42	84	98	8.8
420104000480	40	74	178	1 3/4" - 45	50	105	127	15
420112000480	120	127	330	3 1/4" - 83	83	171	190	70