



Eye Hook Crosby L-320AN

Product information

Features:

- Proper design, careful forging and precision controlled quenched and tempering give maximum strength without excessive weight and bulk.
- Hook extra marked with Deformation Indicators – Two strategically placed marks, one below just the shank or eye and the other on the hook tip, which allows for a QUIC-CHECK™ measurement to determine if the throat opening has changed, thus indicating abuse or overload. To check, use a measuring device to measure the distance between the marks. If the measurement does not meet the dimensions shown below (Deformation Indicator AA), the hook should be inspected further for possible damage.
- Hook extra marked with Angle Indicators – Indicates the maximum included angle which is allowed between two (2) sling legs in the hook.
- Also Available in Carbon steel Grade 4.

Material: Alloy steel

Marking: According to standard, CE-marked

Standard: EN 1677-2

Warning: From WLL 31.5 tons up to 60 tons safety factor = 4.5:1

Safety factor: 5:1

Grade: 8

Part code	WLL ton	Weight kg	Delivery time
401300130190	1.25	0.28	30
401300160190	1.6	0.4	30
401300250190	2.5	0.65	30
401300320190	3.2	0.94	30
401300540190	5.4	1.95	30
401300800190	8	3.76	30
401301150190	11.5	6.8	30
401301600190	16	9.42	30
401302200190	22	17.9	30
401303150190	31.5	27.2	30
401303700190	37	47.6	30
401304500190	45	67	30
401306000190	60	103	30

Blueprint

