

Closed Body Rigging Screws Jaw-Jaw G-6340

Product information

For tensioning of ropes, cables and the like. With eye in both ends.

Certification on request: 2.1, 2.2

... [Read more](#)



Material: Mild steel.

Marking: CE-marked


Finish: Hot dipped galvanized.

Note: End fittings of 6 and 8 mm rigging screws are electro-galvanized.

Safety factor: 5:1

Closed Body Rigging Screws Jaw-Jaw G-6340

Blueprint



Technical data

| Part code | WLL ton | A mm | B mm | C mm | D mm | e mm | f mm | g mm | h mm | Weight kg |
|--------------|---------|------|------|------|------|------|------|------|------|-----------|
| 422100020320 | 0.2 | 6 | 100 | 160 | 240 | 5.5 | 11 | 11 | 6 | 0.13 |
| 422100030320 | 0.32 | 8 | 108 | 175 | 255 | 6 | 12 | 12 | 8 | 0.2 |
| 422100050320 | 0.5 | 10 | 125 | 205 | 300 | 8.5 | 13 | 13 | 8 | 0.6 |
| 422100070320 | 0.7 | 12 | 195 | 320 | 480 | 11 | 30 | 15 | 10 | 0.8 |
| 422100120320 | 1.2 | 16 | 230 | 380 | 555 | 12 | 40 | 20 | 11 | 1.4 |
| 422100150320 | 1.5 | 20 | 270 | 455 | 660 | 16 | 50 | 24 | 12 | 2.4 |
| 422100220320 | 2.2 | 22 | 295 | 495 | 720 | 16 | 50 | 24 | 12 | 3 |
| 422100320320 | 3.2 | 24 | 325 | 540 | 790 | 19 | 56 | 28 | 12 | 4 |
| 422100480320 | 4.8 | 33 | 370 | 660 | 940 | 29 | 70 | 35 | 14 | 9 |
| 422100600320 | 6 | 39 | 400 | 720 | 1.02 | 35 | 80 | 40 | 15 | 11.5 |
| 422100850320 | 8.5 | 45 | 400 | 721 | 879 | 31 | 49 | 49 | 16 | 20.8 |