

Closed Body Rigging Screws Jaw-Jaw G-6340

Product information



For tensioning of ropes, cables and the like. With eye in both ends.

Certification on request: 2.1, 2.2

Material: Mild steel.

Marking: CE-marked

Finish: Hot dipped galvanized.

Note: End fittings of 6 and 8 mm rigging screws are electro-galvanized.

Safety factor: 5:1

Part code	WLL ton	A,	B,	C,	D,	e mm	f mm	g mm	h mm	Weight kg	Delivery time
422100020320	0.2	6	100	160	240	5.5	11	11	6	0.13	10
422100030320	0.32	8	108	175	255	6	12	12	8	0.2	10
422100050320	0.5	10	125	205	300	8.5	13	13	8	0.6	10
422100070320	0.7	12	195	320	480	11	30	15	10	0.8	10
422100120320	1.2	16	230	380	555	12	40	20	11	1.4	10
422100150320	1.5	20	270	455	660	16	50	24	12	2.4	10
422100220320	2.2	22	295	495	720	16	50	24	12	3	10
422100320320	3.2	24	325	540	790	19	56	28	12	4	10
422100480320	4.8	33	370	660	940	29	70	35	14	9	10
422100600320	6	39	400	720	1.02	35	80	40	15	11.5	10
422100850320	8.5	45	400	721	879	31	49	49	16	20.8	10

Blueprint

