

## Modular Spreader Beam MOD 24

---

### Product information



### The standard range

Modular spreader beams provide the ideal solution for most lifting requirements – versatile and cost-effective. Modulift MOD 24 is available with capacity up to 24 t at 5 m and up to 6.5 m at a lower capacity.

[Click here to see the load v span chart for the standard range.](#)

The modular configuration and interchangeable components enable Modulift spreaders to be reused over many lifts. Designed by Modulifts engineering experts and manufactured in their own specialist facilities; the Modulift range are the leading modular spreader beams on the market.

### How the spreader beam is configured

Every Modulift modular spreader beam consists of a pair of end units and a pair of drop links, with interchangeable struts that can be bolted into the assembly between the end units to either lengthen or shorten the beam to suit the requirements of the lift, making them reusable at different spans. The different components are shown in the table below. If you need help to configure your spreader beam, please contact us.

### Load monitoring with Active Link


The innovative Active Link provides wireless real time data by measuring the load at either end of the spreader beam and is ideal for both weighing and dynamic load monitoring. Data is transmitted wirelessly to a USB transceiver that must be connected to a Windows computer or tablet with a spare USB port. The Active Link, which replaces the standard drop link component, offers myriad time, cost and weight advantages.

[... Read more](#)

---

## Modular Spreader Beam MOD 24

### Blueprint



### Technical data

Part code	Type	Weight kg
62080024DL012	Drop Link WLL 12t	5
62080024050	0.50 m Strut	16
62080024EU012	End Unit WLL 12t	17
62080024100	1.0 m Strut	24
62080024200	2.0 m Strut	41
62080024AL12	AL24 Active link 12t	-
6208ALSOFT024	Active link software	-
6208CMOD24	Set of 4 corners	-
62080024BOLTE	Set of bolts, nuts and washers	-