

## Aluminum tripod (excl. fall stop arrester and winch)

---

### Product information



This aluminum tripod is an ideal way of suspension for working in silos, tanks, ditches etc. When combined with a fall stop arrester with a winch, it allows a controlled lowering of persons or in case of emergency, quick pulling up.

#### Optional

- Man-riding or Hand winch (1790509)
- Load winch IKLW 300 (1790510)
- Mounting plate for 41-54W winch (1790511)
- VFall arrest lanyard HRA (1790301)

[... Read more](#)


---

**Marking:** According to standard, CE-marked  
**Standard:** EN 795

# Aluminum tripod (excl. fall stop arrester and winch)


**Blueprint**

Transport length: 1611 mm  
ø Transport: 374 mm



**Position 1**

Height min.: 1590 mm  
ø min.: 645 mm




Height max.: 2594 mm  
ø max.: 1010 mm



**Position 2**

Height min.: 1552 mm  
ø min.: 958 mm



Height max.: 2526 mm  
ø max.: 1561 mm




**Position 3**

Height min.: 1480 mm  
ø min.: 1326 mm



Height max.: 2400 mm  
ø max.: 2207 mm



**Technical data**

| Part code    | Code          | WLL ton | Length m | Model        | Spread positionmm mm | Heightmm mm | Weight kg |
|--------------|---------------|---------|----------|--------------|----------------------|-------------|-----------|
| 825125000370 | 8717365008450 | 0.3     | 2.500    | IK2/1000 Alu | 645 - 2207           | 1480 - 2554 | 24        |