



## Aluminum tripod (excl. fall stop arrester and winch)

### Product information

This aluminum tripod is an ideal way of suspension for working in silos, tanks, ditches etc. When combined with a fall stop arrester with a winch, it allows a controlled lowering of persons or in case of emergency, quick pulling up.

#### Optional

- Man-riding or Hand winch (1790509)
- Load winch IKLW 300 (1790510)
- Mounting plate for 41-54W winch (1790511)
- VFall arrest lanyard HRA (1790301)


**Marking:** According to standard, CE-marked

**Standard:** EN 795


Part code	Code	WLL ton	Length m	Model	Spread position mm	Height mm	Weight kg	Delivery time
825125000370	8717365008450	0.3	2,500	IK2/1000 Alu	645 - 2207	1480 - 2554	24	30

### Blueprint

Transport length: 1611 mm  
ø Transport: 374 mm



**Position 1**  
Height min. : 1590 mm  
ø min : 645 mm



Height max. : 2594 mm  
ø max : 1010 mm



**Position 2**  
Height min. : 1552 mm  
ø min : 958 mm



Height max. : 2526 mm  
ø max : 1561 mm



**Position 3**

Height min. : 1480 mm  
ø min : 1326 mm



Height max. : 2400 mm  
ø max : 2207 mm

