



Aluminum tripod (excl. fall stop arrester and winch)

Product information



This aluminum tripod is an ideal way of suspension for working in silos, tanks, ditches etc. When combined with a fall stop arrester with a winch, it allows a controlled lowering of persons or in case of emergency, quick pulling up.

Optional

- Man-riding or Hand winch (1790509)
- Load winch IKLW 300 (1790510)
- Mounting plate for 41-54W winch (1790511)
- VFall arrest lanyard HRA (1790301)


Marking: According to standard, CE-marked

Standard: EN 795


Part code	GTIN No.	WLL ton	Length m	Model	Spread position mm	Height mm	Weight kg	Delivery time
R1790401	8717365008450	0.3	2,500	IK2/1000 Alu	645 - 2207	1480 - 2554	24	30

Blueprint


Transport length: 1611 mm
 ø Transport: 374 mm



Position 1
 Height min.: 1590 mm
 ø min.: 645 mm



Height max.: 2594 mm
 ø max.: 1010 mm



Position 2
 Height min.: 1552 mm
 ø min.: 958 mm



Height max.: 2526 mm
 ø max.: 1561 mm



Position 3

Height min.: 1480 mm
 ø min.: 1326 mm



Height max.: 2400 mm
 ø max.: 2207 mm

