

## Open Body Turnbuckles Jaw - Oval Eye

### Product information



#### General:

- Standard hot dip galvanized.
- Factory supplied with lock nuts.
- Proof load 2.5 x WLL.
- Straight or in-line pull only.
- Drop forged high tensile steel.
- MBL equals 5x WLL.

Part code	WLL ton	Thread mm	Thread Inch	Take up mm	L min. mm	L max. mm	A, mm	I, mm	K, mm	L, mm	P, mm	U, mm	W, mm	Weight kg	Delivery time
422100230230	0.23	6.35	1/4	102	187	288	121	6	9	20	6	15	11	0.14	30
422100360230	0.36	7.94	5/16	114	221	348	138	8	11	24	6	22	13	0.23	30
422100540230	0.54	9.53	3/8	152	275	427	181	9	13	28	8	22	14	0.36	30
422100100230	1	12.7	1/2	152	312	490	190	11	18	37	10	27	16	0.68	30
422100100235	1	12.7	1/2	229	388	642	266	11	18	37	10	27	16	0.78	30
422100100236	1	12.7	1/2	305	465	795	343	11	18	37	10	27	16	0.94	30
422100160230	1.59	15.9	5/8	152	349	533	200	13	22	44	13	33	20	1.07	30
422100160235	1.59	15.9	5/8	229	425	686	276	13	22	44	13	33	20	1.44	30

422100160236	1.59	15.9	5/8	305	501	838	353	13	22	44	13	33	20	1.64	30
422100240230	2.36	19.1	3/4	152	390	575	210	16	25	53	16	38	24	1.81	30
422100240235	2.36	19.1	3/4	229	470	730	286	16	25	53	16	38	24	2.15	30
422100240236	2.36	19.1	3/4	305	540	880	362	16	25	53	16	38	24	2.69	30
422100240237	2.36	19.1	3/4	457	691	1,186	514	16	25	53	16	38	24	3.18	30
422100330230	3.27	22.2	7/8	305	567	917	307	19	32	60	19	44	29	3.79	30
422100330235	3.27	22.2	7/8	457	720	1,220	523	19	32	60	19	44	29	4.42	30
422100450235	4.54	25.4	1	152	470	670	228	23	36	76	22	52	34	4.05	30
422100450237	4.54	25.4	1	305	620	970	380	23	36	76	22	52	34	5.08	30
422100450236	4.54	25.4	1	457	680	1,260	532	23	36	76	22	52	34	6.03	30
422100450230	4.54	25.4	1	610	930	1,580	685	23	36	76	22	52	34	7.71	30
422100690230	6.89	31.8	1-1/4	305	690	1,050	384	29	46	90	28	71	44	8.81	30
422100690235	6.89	31.8	1-1/4	457	850	1,350	537	29	46	90	28	71	44	11	30
422100690236	6.89	31.8	1-1/4	610	990	1,650	689	29	46	90	28	71	44	12.9	30
422100970230	9.71	38.1	1-1/2	205	725	1,105	400	32	54	103	35	71	52	13.1	30
422100970235	9.71	38.1	1-1/2	457	880	1,410	553	32	54	103	35	71	52	15.9	30
422100970236	9.71	38.1	1-1/2	610	1,030	1,715	705	32	54	103	35	71	52	17.8	30
422101270230	12.7	44.5	1-3/4	457	950	1,410	568	38	60	117	41	86	66	24.4	30
422101270235	12.7	44.5	1-3/4	610	1,100	1,711	721	38	60	117	41	86	66	27.5	30
422101680230	16.8	51	2	610	1,235	1,845	738	45	68	146	51	94	66	40.4	30
422102720230	27.2	63.5	2-1/2	610	1,315	1,925	789	51	79	165	57	113	76	68	30
422103400230	34	70	2-3/4	610	1,370	1,980	789	57	82	177	70	106	92	83	30

**Blueprint**

