Lifting Solutions Group
Axel Johnson International

General duty Thimble POWERTEX PT6899F

Product information



General duty Thimble PT6899F from POWERTEX, intended for general duty steel wire rope slings and synthetic rope end terminations.
Wire rope size 7 – 28 mm.

Standard: Generally according to DIN6899B

... *Read more*


Material: Forged steel
Marking: PX (Powertex), Recommended rope diameter, F (model)
Finish: Hot dip galvanized

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

General duty Thimble POWERTEX PT6899F

Blueprint



Technical data

Part code	Code	Rope Ø range mm	a mm	b mm	C mm	A mm	R1 mm	R2 mm	S mm	t mm	Weight kg
123101100430	PT6899F-11	11	12	15	28	45	6	7.5	3.3	9.5	0.07
123101200430	PT6899F-12	12	13	16	30	48	6.5	8	3.3	10	0.08
123101300430	PT6899F-13	13	14	17.5	32	51	7	8.75	3.7	11	0.12
123101500430	PT6899F-15	15	16	20	36	58	8	10	3.8	12.5	0.16
123101600430	PT6899F-16	16	17	21	38	61	8.5	10.5	4.5	13	0.19
123101800430	PT6899F-18	18	20	24.5	45	72	10	12.25	5.7	15	0.29
123102000430	PT6899F-20	20	22	27	50	80	11	13.5	5.7	16	0.38
123102200430	PT6899F-22	22	24	30	56	90	12	15	6.5	17	0.48
123102400430	PT6899F-24	24	26	33	62	99	13	16.5	6.8	21.5	0.59
123102600430	PT6899F-26	26	28	35	70	112	14	17.5	8	23	0.82
123102800430	PT6899F-28	28	30	37	75	120	15	18.5	8	25.5	1.1

© November 2026 - All Rights Reserved