

Grab Hook GH POWERTEX (with eye)

Product information



The POWERTEX Grab Hook with eye is part of the Powertex G10 Lifting Sling Chain Components range. The Grab Hook is used for shortening lifting chains, and adding them to an assembly makes the lifting chain assembly much more versatile. It enables full WLL because the support wings prevent the lifting chain from deforming.

Available for 6 mm up to 32 mm chain and from WLL 1.4t up to WLL 40t.

Also available as Grab Hook with clevis (GHC) instead of the eye connection.

Powerdex G10 Range benefits:

- 25% higher capacity compared to traditional Grade 8 components
- All POWERTEX G10 components are powder painted in luminous red
- Multi-functional master links and components are included in the range to allow quick and cost-effective assembly of chain slings
- The components meet EN 1677 part 1/2/3/4 +25% WLL
- Each forged component is crack detection tested, and samples are proof load tested.
- Each component is type tested in the factory and fatigue rated to 20,000 cycles at 1.5 times the WLL
- Full traceability through a batch number
- Replacement spare parts available
- All components are chromium 6 free
- POWERTEX 2.2 certificate enclosed with each box of components
- The components may also be used with Grade 8 chain to EN 818-2. In such a case, the chain sling needs to be rated as Grade 8 in accordance with EN 818-4 ... [Read more](#)

Marking: According to standard, POWERTEX + Model (GH-6-10) + traceability code.

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Powder painted in luminous red

Standard: EN 1677-1 (+ 25% WLL), AS 3776

Safety factor: 4:1

Grade: 10

Grab Hook GH POWERTEX (with eye)

Blueprint



Technical data

Part code	Code	Chain diameter mm	WLL ton	EWL mm	D mm	E mm	L mm	L' mm	M mm	W mm	Ø mm mm	Weight kg
402300141370	GH-6-10	6	1.4	46	8	8	73	46	46.5	25.5	13.5	0.15
402300251370	GH-8-10	8	2.5	61	9.5	11	93	61	53	33.5	17.5	0.3
402300401370	GH-10-10	10	4	85	14	13.5	129	85	74	42	22	0.79
402300671370	GH-13-10	13	6.7	104	18.5	17	166	104	96	53.5	27	1.67
402301001370	GH-16-10	16	10	119	22	19	186	119	116	74	36	2.74
402301601370	GH-20-10	20	16	146	23	25	225	146	145	87	44	4.72
402301901370	GH-22-10	22	19	165.5	26	27	260.5	165.5	160.5	90	48.5	8.2
402302651370	GH-26-10	26	26.5	204	34	34	311	204	190	110	52	11.35
402304001370	GH-32-10	32	40	246	40	41	373	246	229	130	64	20.65