CERTEX | Lifting Solutions Group
Axel Johnson International

Anti-slip mats REMA

Product information



REMA®

Forces that are required to hold cargo in place are determined by the coefficient of friction between the different surface materials and, in some cases, dependable on temperature and humidity. Anti-slip mats, used in conjunction with REMA lashings, maximizes the lashing effect and adds to cargo safety.

Properties

- Tested according to German VDI 2700 standard.
- Available in different thicknesses and dimensions.
- Friction coefficient> 0.6.

AS-0.25 / 0.5

- Application: Between load floor and load or between the loads.

AS-2.4

- Price-conscious anti-slip mat.
- Application: In the width of the loading floor of trucks.

AS-13.6 Thin non-slip mat (3 mm),

- Advantage: Cut to size yourself.
- Application: Between loads.

... *Read more*

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Anti-slip mats REMA

Technical data

Part code	GTIN No.	Length m	Model	Dimensions mm	Weight kg
80981460101	8717365007347	0.25	AS-0.25	250 x 8	0.3
80981460103	8717365007354	0.5	AS-0.50	500 x 8	1.7
80981460107	8717365007378	2.4	AS-2.4	200 x 6	2.2
80981460108	8717365261855	13.6	AS-13.6	130 x 3	4
80981460105	8717365007361	5	AS-5.0	250 x 8	8

© November 2026 - All Rights Reserved