CERTEX | Lifting Solutions Group
Axel Johnson International

# Pneumatic vacuum lifters VLA

**Product information**



For horizontal transport of non-porous, stable and flat sheets of metal, plastic and other materials.

**Properties**

- **VLA** types are driven by an pneumatic vacuum pump.

**Safety**:

- Vacuum protection against release.
- Acoustic signal at negative pressure.
- Safety bar for sufficient distance.
- Pressure gauge, vacuum control.
- Acoustic signal included.
- Rechargeable batteries and charger.
- Minimum air pressure must be 6-7 Bar.

**Benefits**:

- Ergonomic action by 1 person.
- Low maintenance.

**Option**

- Manual mechanical rotation and tilting.
- Vacuum lifters for wood and stone on request.
- Higher capacities on request.

**MPORTANT!**

- Always check the material specifications and dimensions (L x W x D) of the sheet or workpiece to be lifted.

... *Read more*

**Marking:** According to standard, CE-mark
**Standard:** EN 12100, EN 13155

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

# Pneumatic vacuum lifters VLA

## Technical data

| Part code | Code | WLL ton | Model | Suction pads quantity / Size mm | Construction height mm | L x Bmm mm | Weight kg |
|---|---|---|---|---|---|---|---|
| 5605 | 8717365022173 | 0.25 | VLA4F-0.25 | 4 x 250 | 620 | 1750 x 1150 | 55 |
| 5605 | 8717365022180 | 0.5 | VLA4F-0.5 | 4 x 300 | 620 | 1750 x 1150 | 55 |
| 5605 | 8717365022197 | 0.5 | VLA6F-0.5 | 6 x 250 | 620 | 2200 x 1200 | 90 |
| 5605 | 8717365022203 | 1 | VLA6F-1.0 | 6 x 300 | 620 | 2200 x 1200 | 90 |
| 5605 | 8717365022210 | 1 | VLA8F-1.0 | 8 x 250 | 620 | 2750 x 1150 | 150 |
| 5605 | 8717365022227 | 1.5 | VLA8F-1.5 | 8 x 300 | 620 | 2750 x 1150 | 150 |

© November 2026 - All Rights Reserved