

## Shank Hook Crosby S-319BN

---

### Product information



- The most complete line of shank hoist hooks. Available 3/4 to 300 metric tons.
- Proper design, careful forging, and precision controlled quench and tempering give maximum strength without excessive weight and bulk.
- Every Crosby Shank Hook has a pre-drilled cam which can be equipped with a latch.
- Hooks incorporate QUIC-CHECK® deformation and angle indicators [... Read more](#)

---

**Material:** Bronze - Quenched and Tempered

**Safety factor:** 4:1

## Shank Hook Crosby S-319BN

### Blueprint



### Technical data

Part code	WLL ton	Hook ID Code	D, mm	F mm	G, mm	H, mm	J mm	K mm	L mm	Mmm mm	Omm mm	Pmm mm	Rmm mm	T mm	X mm	Ymm mm	Z mm	AA*mm mm	O2† mm	T2† mm
420500051410	0.5	†D	72.5	31.8	18.5	20.6	23.6	16	131	16	†23.6	49.8	59.5	24.6	15	52.5	17.5	31.8	-	-
420500061410	0.6	†F	80.5	35.1	21.3	23.9	24.6	18	144	18	†24.6	56.5	66	24.6	19.3	57	19.8	50.8	-	-
420500101410	1	†G	91	38.1	25.4	29.5	26.9	22.4	161	22.4	†26.9	62	70	26.2	18.3	66	22.4	50.8	-	-
420500141410	1.4	†H	102	41.1	29	33.3	30.2	23.9	181	23.9	†29.5	70.5	80.5	29.5	22.4	72	25.4	50.8	-	-
420500201410	2	†I	123	51	36.6	41.4	38.1	33.3	219	28.7	†34.5	88	98	38.9	29.5	87.5	31.8	63.5	25.4	38.1
420500351410	3.5	†J	160	63.5	46.2	52.5	45.2	42.2	265	36.6	40.9	117	121	49.3	35.8	97.5	39.6	76.2	33.3	47.8
420500501410	5	†K	192	76	57.5	67	61	47.8	318	41.4	53	133	149	62.5	46	111	49.3	101	46	57.2
420500651410	6.5	†L	212	82.5	66	74.5	66.5	55.5	409	49.3	57.5	151	162	66	51	178	55.5	101	51	58.7
420501001410	10	†N	263	108	76.5	89	86.5	68.5	461	60.5	76.5	175	207	71.5	65	178	67	127	69.9	65