Lifting Solutions Group
Axel Johnson International

Hoist Ring 8-203

Product information



Rotates through 360° and pivot 180°, rated at 100% at 90°angle.
Load rated parts are 100% magnaflux crack detected.
Individual forged parts and cap screw are traceable to Test Certification.
Bolt are Metric thread (ASME / ANSI B18.3.1M).
Proof tested to 2.5 times the WLL.
Fatigue rated to 1.5 times the WLL.
Quick and simple assembly, just a tapped hole is required.

... *Read more*

Material: Manufactured from forged alloy steel, quenched and tempered.
Marking: According to standard, CE-mark
Standard: EN 1677-1

Safety factor: 4:1

© November 2026 - All Rights Reserved

CERTEX Lifting Solutions Group
Axel Johnson International

Hoist Ring 8-203

Blueprint



Technical data

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	M mm	Weight kg
42158203004	0.5	M8x1.25	10	40	41	41	10	17	101	65	M8	0.4
42158203005	0.55	M10x1.5	16	40	41	43	10	11	101	65	M10	0.5
42158203010	1.3	M12x1.75	38	65	59	57	15	15	157	104	M12	1.7
42158203019	2.4	M16x2	81	65	59	61	15	20	157	104	M16	1.8

© November 2026 - All Rights Reserved