CERTEX | Lifting Solutions Group
Axel Johnson International

Triple Swivel Ring Codipro TSR

Product information



The TSR ring is a triple swivel model with two pivots. It can be used for smooth tilting, turning and flipping, The optimised design prevents any damage to the sling and load while the ring is swivelling and ensures perfect alignment with the sling. However, the TSR triple swivel ring is not recommended for lengthy rotations of full loads.

It consists of a steel ring that has a rotating range of 360°.

- Maximal articulation
- Move the hook away from the load to lift
- Optimal hook position

... *Read more*

Marking: According to standard, CE-mark
Temperature range: -20°C up to + 200°C
Standard: EN 1677-1
Note: M48 - M56 have SF 4:1

Safety factor: 5:1

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Triple Swivel Ring Codipro TSR

Blueprint



Technical data

Part code	WLL ton	Thread	Torque Nm	Standard L1 mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L1 mm	S1 mm mm	S2 mm mm	X mm	Weight kg
4215TSRM8	0.4	M8 (x1,25)	6	15	33	56	30	41	25	10	58	9.5	15	8	16	18	0.4
4215TSRM10	0.7	M10 (x1,50)	10	18	33	56	30	41	25	10	58	9.5	18	8	16	18	0.4
4215TSRM12	1.05	M12 (x1,75)	15	21	33	56	30	41	25	10	58	9.5	21	8	16	18	0.4
4215TSRM14	1.4	M14 (x2)	30	23	45	81	45	48	34	16	79	13	23	8	20	24	1.1
4215TSRM16	2	M16 (x2)	50	27	45	81	45	48	34	16	79	13	27	8	20	24	1.2
4215TSRM18	2.3	M18 (x2,5)	70	27	45	81	45	48	34	16	79	13	27	8	20	24	1.2
4215TSRM20	2.5	M20 (x2,5)	100	30	45	81	45	48	34	16	79	13	30	8	20	24	1.2

© November 2026 - All Rights Reserved