



## Panzerband

### Product information



Panzerband is a wire mesh sling made of riveted chain links. Produced in specialised steel, it offers a safety factor of 4. Unlike other products, the mesh is riveted rather than welded thus avoiding the need to replace the entire sling when damaged.

Wire mesh slings are very flexible and adapt perfectly to different forms of loads. They are heavy-duty, slash-resistant and wide enough to be able to handle thin-walled sheets, without any risk of damaging lower sheets.

Mesh slings are highly effective when used for “basket handling” as they neatly encircle the load. LIFTEUROP also provides a sliding fastener so the sling can be used as a “slip knot”. Available in stainless steel or aluminium and fitted with a protective PVC sheath.

The wire mesh sling comes with an EC declaration and is readily available. It has legible marking and an individual traceability code.

Machinery Directive 2006/42/CE

**Marking:** CE-marked

**Temperature range:** -20°C up to +100°C

**Safety factor:** 4:1

Part code	WLL ton	EWL m	Type	A mm	B mm	C mm	L mm	Weight kg	Delivery time
3901421B	1.5	1	PZR 6	75	55	36	1,000	4	14
3901421C	2	2	PZR 8	90	60	45	2,000	8	14
3901422A	3	2	PZK 6	105	70	45	2,000	19	14
3901422B	4	3	PZK 8	120	80	55	3,000	23	14
3901422C	5	3	PZK 10	120	80	70	3,000	27	14
3901422D	7.5	3	PZK 15	150	100	105	3,000	43	14
3901422E	10	4	PZK 20	180	120	140	4,000	70	14
3901422F	12.5	4	PZK 25	200	135	175	4,000	89	14
3901422G	15	4	PZK 30	225	150	210	4,000	108	14