

Transition Link Pewag BW

Product information



For pewag welded system.

Intermediate link or transition link and securing link.

... [Read more](#)

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.


Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Transition Link Pewag BW

Blueprint



Technical data

Part code	Code	WLL ton	EWL	dmm mm	t mm	w mm mm	smm mm	Weight kg
402200100120	BW 7	1	36	7	36	16	-	0.03
402200140120	BW 8*	1.4	36	8	36	16	-	0.05
402200190120	BW 9	1.9	44	9	44	20	-	0.07
402200250120	BW 10	2.5	44	10	44	20	-	0.09
402200400120	BW 13	4	54	13	54	25	10	0.17
402200670120	BW 16	6.7	70	17	70	34	14	0.39
402201000120	BW 20	10	85	20	85	40	14	0.63
402201250120	BW 22	12.5	115	23	115	50	17	1.16
402201400120	BW 23*	14	115	27	140	50	20	1.92
402201620120	BW 26	16.2	140	27	140	65	20	1.92
402201900120	BW 27*	19	140	36	170	75	-	4.35
402202650120	BW 32	26.5	150	33	150	70	26	3.16
402203100120	BW 36	31	170	36	170	75	-	4.35
402204040120	BW 40	40.4	170	40	170	80	-	4.12
402206400120	BW 50	64	200	50	200	100	-	10.58